

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

LARIX

TECHNICAL CHARACTERISTICS

Available Formats:	10x60, 6x30 and 24x24 Baita Pattern		
Style Description:	Modern Wood	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Textured Wood	Number of Faces/Screens:	60
Thickness in mm:	10	Number of Punches/Molds:	N/A
Modular Suitability:	10x60: 63%, 6x30: 37%	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte/Textured
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8 th

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: 0.67 Dry: 0.88
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.56
Scratch Hardness (MOHS)	NPD	Breaking Strength:	Conforming ISO 10545-4
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Conforms		

PACKING INFORMATION - 6x30 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	8.48	Pieces per Carton:	7
SqFt per Pallet:	407.04	Pounds per Carton:	38.5 lbs
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".