



## Product Data Sheet CLOSED LOOP TREATMENT LT-2300

the required amount of product. LT-2300 is normally applied to supplement an existing product dosage. The recommended product use rate or application will be made by your Clear Water Technologies representative.

### DESCRIPTION

LT-2300 is an easy to apply concentrated liquid azole supplement to provide additional corrosion protection for yellow metals in cooling water or closed loop systems. The active azole quickly films the metal surface to provide maximum corrosion inhibition at low dosages.

### APPLICATION

LT-2300 is designed for use in closed loop systems as a supplement or adjunct to an existing program where additional azole or yellow metal inhibitor is required. LT-2300 is also designed for use as a supplement for open recirculating cooling water systems that require higher than normal levels of yellow metal inhibitor.

### PHYSICAL PROPERTIES

Color & Form..... Amber liquid  
Specific Gravity ..... 1.087 grams/ml  
pH (neat) ..... 12.4  
Density ..... 9.06 lbs/gal.  
Odor ..... Sweet

### DOSAGE & FEEDING

LT-2300 may be fed in a slug dose fashion using a pot feeder or by means of a chemical metering pump, to deliver

### HANDLING & PRECAUTIONS

LT-2300 is a highly alkaline liquid product. Contact with eyes, skin and clothing should be avoided. Wear goggles or face shield, rubber gloves and rubber apron when handling. Wash thoroughly after handling. Do not store near strong acids or oxidizers. Clean up spills immediately. Rinse container before re-use or disposal.

### PACKAGING

LT-2300 is available in:  
5-gal polyethylene pails.... net wt. 45 lbs.