

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	TIVOLI- MATTE
------	--------	---------------

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Travertine	Number of Faces/Screens:	40
Thickness in mm:	8.5	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	N/A
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No (Pressed)		

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	< .5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)	N/A	Breaking Strength:	250 lb. or Greater
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Resistant		

PACKING INFORMATION - 12x24 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	19.80	Pieces per Carton:	10
SqFt per Pallet:	792.00	Pounds per SqFt:	3.86
Boxes per Pallet:	40.00	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	TIVOLI- POL
------	--------	-------------

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Travertine	Number of Faces/Screens:	40
Thickness in mm:	8.5	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	N/A
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Glossy/Flat
Rectified:	Yes (Polished only)		

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	< .5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	250 lb. or Greater
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Resistant		

PACKING INFORMATION - 12x24 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	19.80	Pieces per Carton:	10
SqFt per Pallet:	792.00	Pounds per SqFt:	3.86
Boxes per Pallet:	40.00	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".