

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Geo

## TECHNICAL CHARACTERISTICS

Available Formats:	30x30, 15x30, 3x3 Mosaic 12x12 Sheet, 3x3 Bullnose		
Style Description:	Marble Porcelain	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	10- 15x30 & 15-30x30
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	Yes	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.1%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)		Breaking Strength:	1800-2400
Frost Resistant:	Resists	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Conforms to Standard		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.20	Pieces per Carton:	3
SqFt per Pallet:	509.60	Pounds per Carton:	89.73
Boxes per Pallet:	28	SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".