

# Improved Stock

## 9,500 RPM Points Class

- Optional Points class. Cost \$100.00 per tractor Entry Fee for the year.
- Stock appearing engine & sheet metal, transmission, and rear end must match brand.
- Must have factory built wide front steer axle from any brand (tractor), No combine steering axles
- No truck parts allowed. Must use all Ag parts. 410 cubic inch max. Engine block must be from a 410 cubic inch or smaller. Mandatory cubic inch check prior to the season starting if you plan on participating in the class for points. \$100.00 Tech Fee.
- Stock appearing carburetors & rotary fuel injection pumps. No inline fuel injection pumps allowed in this class.
- One fuel only diesel or gas, No pressurized fuels, nitrous oxide or other oxidizing agents allowed.
- A Single T4 flange turbocharger is allowed with up to a 2.25 inch max intake. Turbo inlet vanes must protrude 1/8" into the max 2.25" intake bore. (No slots or slugs allowed)
- Exhaust must be cross bolted after turbo.
- Cross over pipe max length 40" and max diameter 3.78".
- Water injection allowed. Water and lube product only, no additional additives.
- No inner coolers allowed.
- No speed or RPM limit.
- 18.4 x 38 max tire size. No V, single, or double cut tires.
- No weight can extend 24" beyond the furthest most stock point of the front end of the tractor.
- **Allowed:** Pulling hitch, Weld on hubs, steel wheels, Radial tires, Aluminum front wheels, & weight brackets.
- **Not allowed:** Duals, curved exhaust pipes, Aluminum frame / chassis.
- Tractor **must** have wheelie bars and ROPS with seatbelt.
- Tractor **must** be equipped with an emergency air shutoff on the inlet of the turbo.
- Tractor **must** have metal side shields covering motor assembly for safety reasons.
- Strongly recommended spring loaded deadman's throttle
- **Over 3000 RPM must have the following safety equipment: Steel flywheel and necessary shields for rotating components**
- Base of seat, ROPS, and roll cages must be properly secured to the tractor
- Helmet is required if tractor is equipped with a roll cage or narrow ROPS
- No helmet required if equipped with a factory width ROPS.
- Fire extinguisher required and mounted for easy accessibility.
- Tractor must be available for tech inspection at all times before or after pull. No exceptions.
- Class weight is 9,500 lbs plus 200 lbs allowance for driver. (Max weight 9,700 lbs)