

INSTALLATION INSTRUCTIONS

PLACEMENT OF WALL MOUNT: The #3001 Wall Mount for the #300 DIRECTOR Shower should be mounted within 36" of the water supply hose inlet connection when standard 40" hose is used. (If 59" hose is used, 48" is the recommended distance.) Slot in the nylon socket should point down; fasten bracket to wall with two oval head screws.*

FINAL CONNECTIONS: Attach the hose to connections, using gaskets provided. Only moderate pressure is required when you are tightening, as gaskets form actual seal. (If a wrench or pliers are used, protect the chrome finish with a cloth over the jaws.)

VOLUME CONTROL VALVE: (Accessory) Attach volume control valve between hand spray and hose using gaskets provided.

GUARANTEE: Complete your guarantee card and mail promptly.

PARTS LIST

Part No.	Description
3001	Shower Mount Complete
430 NL	Nylon Hand Shower Complete w/connection
46IN P/B	Nylon Hand Shower Complete w/Push Button Volume Control
495-40	Chrome Hose w/gaskets, 40" long (Standard)
495-59	Chrome Hose w/ gaskets, 59" long (Optional)
4951	Gasket, all connections
4952	Gasket for Spray Disc
4611	Stainless Steel Spray Disc
476	Volume Control Valve (Accessory)
3002	Elbow for Hand Shower

*Brass, 1" x #10, oval head, chromed wood screws are furnished with each unit when requested.