


LED Light Specification

BRAVOLIGHT.com (813) 598-2076

100 Watt LED Gas Canopy Fixture

Applications: Wherever current HID fixtures are used



| | |
|--------------------------|--|
| Color Temperature (CCT): | Natural / Day 4500K / 5800K |
| Watts: | 100 W |
| LED's: | Ultra-bright Osram  |
| Input Voltage A/C: | 120 - 277 |
| Operating Temp Range: | -40° - 190° |
| CRI: | 70> |
| Lumens: | 8,300 |
| Benefits: | Lower power bills, eliminate bulb replacement |
| Features: | Surge protection, safety cable, O-rings CSA certified for US and Canada Flush mount bracket available |
| Power Factor: | >95% |
| IP Rating: | 65 |
| Mounting: | Direct mount is suitable for use in single or double skin canopies with a minimum 4.0" (102mm) wide panels and a minimum 22 gauge, 0.030" (0.7mm) canopy thickness |
| Optics: | 120° beam angle |
| Typical HID Replacement: | Up to 400W |
| Typical Mounting Height: | up to 20 feet |
| Dimensions: | 15"W X 15"L X 3"H |
| Weight: | 16 lbs. |
| Finish: | White powder-coat over Chromate Conversion |
| Warranty: | 60 months from purchase |
| Rated Life: | 50,000 hours + |

Installation:

For replacement of existing HID fixtures. Connect 120 – 277 VOLTS A/C directly to fixture. Professional installation recommended. No modifications allowed to fixture as this could cause damage to heat-sink, loosen electronics, and void warranty. Do not look directly at light at close range – very bright. All Bravolight products are certified CE & RoHS.



7/1/2015

BVOB-GAS-100W-FLAT