

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**Metropoli**

## TECHNICAL CHARACTERISTICS

Available Formats:	32x32, 16x32, 3x32 Floor Bullnose		
Style Description:		Glaze Application Method:	
Visual Characteristics:	Contemporary	Number of Faces/Screens:	7
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	Yes	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<0.42
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Resists		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.46	Pieces per Carton:	2
SqFt per Pallet:	659.54	Pounds per Carton:	54.378
Boxes per Pallet:	49	SqFt per Container:	1390.80
Pallets per Container:	20		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".