

Multiax NE Door Machine





- Size
- Bevel
- Trim
- Ease
- Machine Most Styles Hinges
- Machine Lights
- Machine Sweeps & Peeps
- Machine Closures
- Machine Most Styles Locks
- Complete Software Package





CNC Machining Center for Sizing and Machining Doors

NE Doors

MULTIA



Equipped with a 13 HP Spindle and 7 Vertical and Four Horizontal **Independent Drill Unit**

Traveling Automatic Tool Changer Magazine with 8 to 16 Tools

Optional Integrated

Tool Touch Off







OSAI Open with Integrated PC



C Axis on Spindle Motor Allows for Rotational Axis Control of Aggregates





Underneath Aggregate



4 Exit Horizontal Aggregate



Heavy Duty Two Exit Aggregate



4 Exit 87 Degree Aggregate



Axes Strokes X 3,850 mm (151") Y 1,850 mm (72.8")

Rapid Speeds X 70 M/min. (2,756")

Door Size

1,850 mm (72.8") 400 mm (15.7") C +/- 360 Degrees Continuous

Y 70 M/min. (2,756") **Z** 20 M/min. (787") **C** 30 RPM

Minimum 10" x 30" Maximum 48" x 120"

Standard CNC: OSAI Open with Integrated PC

Standard Spindle: 13 hp, 1,000-24,000 RPM

Automatic Tool Changer: 12 Tools

Special Door Fixture Includes:

- CNC Controlled Fixture Positioning to Adjust to the Door Width.
- Reference Stops Designed to Handle Overhanging Laminates.
- . Pop Up Rollers for Easy Loading and Unloading.
- Removable Vacuum Pods When Performing Through Cutting.
- Center Rail Designed for Splitting Doors.
- Fixture Designed to Machine Up To a 48" x 120" Door.
- · Able to Size, Bevel, Trim, and Machine Hinges, Lights, Sweeps, Peeps, Closures, All Styles Locks, ETC.