



Ideal standard size Convection ovens offer a solid construction and versatility for different types of cook preparation with set temperatures and cook times 20-30% lower than regular static ovens. The independent door assembly provides wide door opening with no restrictions and free from the servicing, usually associated with chain driven doors. Available in single unit or double deck options.



STANDARD FEATURES

- Three (3) inshot burners rated at 18,000 BTU/hr ea.
- Nat. Gas built with LP conversion kit.
- Independent large doors with full view windows.
- 2 speed, 1/2 HP fan motor (1725 & 1140 RPM)
- Porcelain enamel interior oven
- Ten (10) position interior rack guides.
- Five (5) nickel plated oven racks.
- Fenawal electronic ignition.
- Electronic thermostat and manual timer controls.
- 150 F to 500 F temperature range (66 C to 260 C)
- Control panel located away from burners (right side) and opens downward for easy service.
- Two (2) Halogen interior lights.
- Oven ready light.
- Stainless Steel sides, front and top.
- Forced "cool down" fan mode control.
- One (1) year parts and labor warranty (only in Continental USA).
- Electrical: 120/60/1 HP, 6 ft. cord and 3 prong plug (NEMA#5-15P)



Model: IDCO-2 (w/ Mounting Kit included)

| Model | Overall Dimensions | | | Oven Interior | | | Rack Clearance | | Shipping Crate | | | | | List Price |
|--------|--------------------|--------|--------|---------------|-------|--------|----------------|-------|----------------|--------|--------|-------------|-------|-------------|
| | Width | Depth | Height | Width | Depth | Height | Width | Depth | Width | Depth | Height | Volume | Width | |
| IDCO-1 | 38.0" | 30.5" | 32.0" | 29.0" | 22.5" | 28.25" | 28.25" | 22.0" | 48.0" | 42.0" | 39.0" | 45.5 cu.ft. | 29.0" | \$9,590.00 |
| | 965mm | 775 mm | 813mm | 737mm | 572mm | 508mm | 718mm | 559mm | 1220mm | 1067mm | 991mm | 1.30cu.ft. | 737mm | |
| IDCO-2 | 38.0" | 30.5" | 70.0" | 29.0" | 22.5" | 20.0" | 22.5" | 22.0" | 48.0" | 42.0" | 80.0" | 112 cu.ft. | 29.0" | \$18,230.00 |
| | 965mm | 775 mm | 1778mm | 737mm | 572mm | 508mm | 572mm | 559mm | 1220mm | 1067mm | 2032mm | 2.50cu.ft. | 737mm | |

Note: Set of (4) Legs with Casters for single Convection Oven Net \$175.00
 Set of (4) Heavy Duty Casters with kit for Double Stack Convection Oven, Net \$205

Gas: 3/4" NPT rear gas connection, specify type of gas and altitude if over 2,000 feet.
 Pressure: 5" W.C. - Natural Gas
 10" W.C. - Propane Gas
 Note: Install the pressure regulator supplied with the appliance, at the inlet of the gas line.