

J&B PART NUMBER

V9176

SAFETY DATA SHEET.

Issuing date 28-Apr-2017

Revision Date 04-May-2018

Version 10

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 4777 RUST BUSTER PENETRANT-VOC COMP

Recommended use of the chemical and restrictions on use

Product code 4777

Product Type Extremely Flammable Aerosol
Synonyms None

Supplier's details

Recommended Use Penetrating Oil.
Uses advised against No information available

Manufacturer:
International Epoxies & Sealers
P.O. Box 185
San Antonio, FL 33576
Phone: 1-800-451-7206

Emergency telephone number
Chemical Emergency Phone Number INFOTRAC: 1-800-535-5053 (NORTH AMERICA)
INFOTRAC: 1-352-323-3500 (INTERNATIONAL)

2. HAZARDS IDENTIFICATION

Classification


Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements
 Harmful if inhaled
 Causes skin irritation
 Causes serious eye irritation
 May cause respiratory irritation. May cause drowsiness or dizziness.
 May be fatal if swallowed and enters airways
 Extremely Flammable Aerosol
 Contains gas under pressure; may explode if heated



Appearance Opaque **Physical state** Aerosol **Odor** Fragrance

Precautionary Statements - Prevention

- Wear eye protection / face protection / protective gloves
- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. -No smoking
- Do not spray on an open flame or other ignition source.
- Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

- Specific treatment (see first aid on this label)
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention
- Take off contaminated clothing and wash it before reuse
- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Immediately call a POISON CENTER /doctor/physician
- Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

0 00001021% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	40-50
HYDROTREATED LIGHT DISTILLATES	64742-47-8	20-30
PROPANE/SOBUTANE/N-BUTANE	68476-86-8	10-20
2-BUTOXYETHANOL	111-76-2	1-10
PETROLEUM DISTILLATES	64742-47-8	1-10
KEROSENE	8008-20-6	1-10
MINERAL OIL, DEWAXED	64742-65-0	1-10
ETHYLENE GLYCOL	107-21-1	<0.1
NAPHTHALENE	91-20-3	<0.01

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Wash skin with soap and water. Remove and wash contaminated clothing before re-use. Get medical attention if irritation persists.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms	Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
----------------------	---

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog. Dry chemical. Foam. Carbon dioxide (CO₂). Cool containers / tanks with water spray. Water fog Dry chemical. Foam Carbon dioxide (CO₂). Cool containers/tanks with water spray. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Cool containers / tanks with water spray. Keep away from sources of ignition - No smoking

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Extremely Flammable / Flammable. In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire, cool tanks with water spray.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
PROPANE/SOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm ppm (vacated) TWA: 1900 mg/m ³	74-98-6 IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
KEROSENE 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m ³
MINERAL OIL, DEWAXED 64742-65-0	ACGIH TLV: 5 mg/m ³ (oil mist)	OSHA PEL: 5 mg/m ³ (oil mist)	-
ETHYLENE GLYCOL 107-21-1	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Fragrance
Appearance	Opaque	Odor Threshold	
Color	Dark Green		
<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range			
Flash Point	-97 °C / -142 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit			
lower flammability limit			
Vapor pressure			
Vapor density			
Specific Gravity	0.782		
Water solubility	Negligible		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available	Not applicable	
Decomposition temperature			
Viscosity	No information available		
Explosive properties			
<u>Other information</u>			
VOC Content(%)	24.88		

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides, Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation.

Ingestion May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	=31mg/L (Rat) 4 hr
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
ETHYLENE GLYCOL 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)	-
NAPHTHALENE 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h

Information on toxicological effects

Symptoms Harmful if inhaled. Causes skin and serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.

Eye damage/irritation Irritating to eyes.

Sensitization Not a known sensitizer.

Germ Cell Mutagenicity Not a germ cell mutagen.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-BUTOXYETHANOL 111-76-2	-	Group 3	-	-
NAPHTHALENE 91-20-3	A3	Group 2B	Reasonably Anticipated	-

*IARC: (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

Reproductive toxicity This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ systemic toxicity (repeated exposure) No known effect based on information supplied.

Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target Organ Effects Respiratory System, Central nervous system (CNS).

Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity	0.0001021% of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document	
ATEmix (oral)	4493 mg/kg
ATEmix (dermal)	20532 mg/kg
ATEmix (inhalation-dust/mist)	31.7 mg/l
ATEmix (inhalation-vapor)	9 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h
PETROLEUM DISTILLATES 64742-47-8	-	45 mg/L LC50 Pimephales promelas 96h flow-through 2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static	-	-
MINERAL OIL, DEWAXED 64742-65-0	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
ETHYLENE GLYCOL 107-21-1	6500 - 13000 mg/L EC50 Pseudokirchneriella subcapitata 96h	41000 mg/L LC50 Oncorhynchus mykiss 96h 14 - 18 mL/L LC50 Oncorhynchus mykiss 96h static 27540 mg/L LC50 Lepomis macrochirus 96h static 40761 mg/L LC50 Oncorhynchus mykiss 96h static 40000 - 60000 mg/L LC50 Pimephales promelas 96h static 16000 mg/L LC50 Poecilia reticulata 96h static	-	46300 mg/L EC50 Daphnia magna 48h
NAPHTHALENE 91-20-3	-	5.74 - 6.44 mg/L LC50 Pimephales promelas 96h flow-through 1.6 mg/L LC50 Oncorhynchus mykiss 96h flow-through 0.91 - 2.82 mg/L LC50 Oncorhynchus mykiss 96h static 1.99 mg/L LC50 Pimephales promelas 96h static 31.0265 mg/L LC50 Lepomis macrochirus 96h static	-	2.16 mg/L LC50 Daphnia magna 48h 1.96 mg/L EC50 Daphnia magna 48h Flow through 1.09 - 3.4 mg/L EC50 Daphnia magna 48h Static

Persistence and degradabilityBioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
2-BUTOXYETHANOL 111-76-2	0.81
ETHYLENE GLYCOL 107-21-1	-1.93
NAPHTHALENE 91-20-3	3.6

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D
or QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	Not listed	X	X	X	X
HYDROTREATED LIGHT DISTILLATES	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	x	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X

PETROLEUM DISTILLATES	X	X	X	x	X	X	X	X
KEROSENE	X	X	X	x	X	X	X	X
MINERAL OIL, DEWAXED	X	X	X	X	X	X	X	X
ETHYLENE GLYCOL	X	X	X	X	X	X	X	X
NAPHTHALENE	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 CHINA - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	1-10	1.0
ETHYLENE GLYCOL - 107-21-1	107-21-1	<0.1	1.0
NAPHTHALENE - 91-20-3	91-20-3	<0.01	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
NAPHTHALENE 91-20-3	100 lb 1 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is {are} known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
ETHYLENE GLYCOL - 107-21-1	Developmental (ingested) <0.1%
NAPHTHALENE - 91-20-3	Cancer <0.01%

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-BUTOXYETHANOL 111-76-2	X	X	X
KEROSENE 8008-20-6	X	X	X
ETHYLENE GLYCOL 107-21-1	X	X	X
NAPHTHALENE 91-20-3	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

- WHMIS Hazard Class**
 A Compressed gases
 B5 Flammable aerosol
 D2B Toxic materials

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards N/A
HMIS Health Hazard 2* Flammability 4 Physical Hazard 1 Personal protection B
Chronic Hazard Star Legend *Chronic Health Star Hazard Chlorinated solvents Severe overexposure may cause liver or kidney damage. Repeated or prolonged exposure may cause central nervous system damage*

Prepared By International Epoxies & Sealers
 30241 Commerce Drive
 San Antonio, FI 33576
 Tel 800-451-7206

Issuing date 28-Apr-2017
Revision Date 04-May-2018
Revision Note
 (M)SDS sections updated 15

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet