


SINGLE PHASE CONTROL TRANSFORMER - T SERIES



IP2X **RoHS** **AS/NZS** **CE**
Input Voltage: 240VAC \pm 5%
Output Voltage: 24VAC
Frequency: 50/60Hz
Rating: 20VA - 1000VA
Temperature Rise: 60°C



DATA OUTLINE

Rating	A x B x C (mm)	D	E	F	G	H x H	Kg	Enclosure
20VA**	67 x 58 x 65	70	N/A	1.0	24	5 x 8	0.9	EN1 - 25
40VA	78 x 72 x 95	56	46	1.2	18	4.6 x 8	1.4	EN1 - 25
63VA	78 x 72 x 95	56	46	1.2	18	4.6 x 8	1.5	EN1 - 25
100VA	87 x 75 x 98	64	62	1.5	16	4.6 x 8	1.8	EN1 - 31
160VA	96 x 92 x 110	84	74	1.5	16	5.8 x 10	2.5	EN1 - 38
250VA	96 x 100 x 110	84	85	1.5	16	5.8 x 10	3.4	EN1 - 38
400VA	120 x 100 x 130	90	85	2.0	16	5.8 x 10	5.6	EN1 - 44
630VA	150 x 110 x 155	122	90	2.0	18	7 x 14	8.4	EN1 - 50
800VA	150 x 130 x 155	122	105	2.0	18	7 x 14	9.5	EN1 - 50

** 20VA does not have \pm 5% taps
 Mounting is by 2 point saddle bracket