



ERADS-DTA-7588TC29.7P110
REV2.0
DATE: 25/09/23

ERA TorQ

7 5/8 BTC 29.7ppf P110

Pipe

Plain End Weight	Wall Thickness	Inside Diameter	Drift Diameter	Pipe grade	Body Yield Strength	Internal Yield Plain End	Collapse Pressure
Lbs/Ft	Inches	Inches	Inches		Lbs	PSI	PSI
29.70	0.375	6.875	6.750	P110	940,000	9,470	5,350

Connection Dimensions with ring

Coupling Outside Diameter	Connection Yield Strength	REGULAR Coupling Length	REGULAR Make-up Loss	ERA TorQ ring height	ERA TorQ ring OD	ERA TorQ ring ID
Inches	Lbs	Inches	Inches	Inches	Inches	Inches
8.500	960000	10.375	4.688	0.921	7.310	6.875

Torque

FT LBS APPLIED	Min Make up	MAX NO TORQUE TURN	MAX WITH TORQUE TURN	<p>Note 1: For maximum field efficiency ensure that TT computer monitoring is used if maximum torque figure is required. Note 2: Delta torque yield point of torque ring is 44424 ftlbs. This means that the torque ring will collapse if you apply 44424 ftlbs of Delta torque into the torque ring itself, excluding your pin / ring contact torque with triangle down.</p>
PIN / RING CONTACT	7,630	7,630	7,630	
DELTA TORQUE	8884	17,769	22,212	
Total	16,514	25,399	29,842	

For further information on field application parameters please contact:
 ERA Oilfield Service (Thailand) Co Ltd., 66/69 Moo 4, Soi 17, Phayun, Ban Chang, Rayong, Thailand 21130.
 Tel: +66 8 4345 8730 Email: jim.reid@eraoilfieldservices.com