# MULTI-MEDIA FILTRATION

- Available individually or as part of a total water treatment solution
- Full scope of materials of construction for any application fiberglass, PVC, CPVC, lined carbon steel, and stainless steel
- · Flexibility in controls: independent or part of a central control system
- Efficient component layout allows for ease of maintenance and calibration
- Customizable to customer special cations for valves, instruments and other mechanical components SUSPENDED VAL SUSPERENOVAL
- Optional complete validation package with IQ/OQ protocol execution
- Supported by Basiia 24-hour customer service •
- Backed by warranty

## Standard Features

- Valve nest or multi-port valve configurations
- Reduced number of terminal point
- Reduces site piping costs and time
- Generous freeboard
- Reduces media loss during backwash
- Specialized distributor and under-drain design
- Ensures proper ow distribution
- No downstream resin trap or filter required
- Heat sanitizable: hot water or steam arrangements available
- Optional PLC based controls

## Equipment Details

- Pneumatic panel houses all pneumatic components
- Premium valves and instruments
- Polypropylene or stainless steel air lines
- Stainless steel hardware



باسية للمقاولات **Basia Contracting** 

MODE

MMF-MMF-0

MMF-1

Notes:

• All vessels are available in carbon steel lined with Plasite 7159 and 316L stainless steel.

• Piping on fiberglass and carbon steel vessels is

WWW.BASIIA.COM sales@basiia.com

| MODEL   | DIAMETER IN | FLOW RANGE IN      |
|---------|-------------|--------------------|
|         | INCHES [MM] | GPM [LPM]          |
| MMF-012 | 12 [305]    | 2-9 [8-34]         |
| MMF-018 | 18 [457]    | 4-21 [15-79]       |
| MMF-024 | 24 [610]    | 6-38 [23-144]      |
| MMF-030 | 30 [762]    | 10-59 [38-223]     |
| MMF-036 | 36 [914]    | 14-85 [53-322]     |
| MMF-042 | 42 [1067]   | 19-115 [72-435]    |
| MMF-048 | 48 [1219]   | 25-151 [95-572]    |
| MMF-054 | 54 [1372]   | 32-191 [121-723]   |
| MMF-060 | 60 [1524]   | 39-236 [148-893]   |
| MMF-066 | 66 [1676]   | 48-285 [182-1079]  |
| MMF-072 | 72 [1829]   | 57-339 [216-1283]  |
| MMF-078 | 78 [1981]   | 66-398 [250-1507]  |
| MMF-084 | 84 [2134]   | 77-462 [297-1749]  |
| MMF-090 | 90 [2286]   | 88-530 [333-2006]  |
| MMF-096 | 96 [2438]   | 101-603 [382-2283] |
| MMF-102 | 102 [2591]  | 113-681 [428-2578] |
| MMF-108 | 108 [2743]  | 127-763 [481-2888] |
| MMF-114 | 114 [2896]  | 142-851 [538-3221] |
| MMF-120 | 120 [3048]  | 157-942 [594-3566] |

• Vessels up to 48" (1219 mm) in diameter are available in fiberglass.

available in PVC, CPVC and 316L stainless steel.

Piping on 316L stainless steel vessels is available in 316L stainless steel.