



Octowet 75PG

CHEMICAL DESCRIPTION: Sodium dioctyl sulfosuccinate
(CAS # 577-11-7)

PHYSICAL FORM: Octowet 75PG is a 75% solution (75% DOSS)
in water and propylene glycol.

PRODUCT SPECIFICATIONS

METHODS

Solids, %	74.0 – 76.0	WI-SCC-041
pH	5.0 – 7.0	WI-PHC-010
Color, APHA	0 - 50	WI-CDC-520
Acid Number	0 - 2.5	WI-ACC-030

PRODUCT DESCRIPTION:

Octowet is very effective at low concentrations for applications as a high-speed wetting agent in dyeing and washing operations for the textile industry. Octowet is widely used as a penetrant and emulsifier for many textile applications in the areas of preparation, dyeing, and finishing. Octowet 75PG is formulated so as to provide the surfactant in a non-flammable aqueous form. The recommended use level is .50 – 2.0 parts per hundred. VOC's are 7.0 – 8.0 %.

Sodium dioctyl sulfosuccinate is compliant for use under the following: CFR 21, Sections: 175.105, 175.300, 176.170, 176.210, 177.1200, 177.2800, and 178.3400.

Octowet 75PG is listed for use under the following CFR 21 Sections: 175.300, 176.180, 175.105, 176.170, 176.210, and 178.3400. It is the responsibility of the manufacturer of the FINAL article to ensure that the article complies with the extraction limitations and other limitations, including use limitations, applicable to its intended use and is technically suitable for that particular use.

All of the ingredients used in Octowet 75PG are listed on TSCA inventory, Australian AICS, Canadian DSL, European EINCES/ELICS/NLP, Japanese ENCS/MITI/ISHL, Chinese IECSC, Korean KECI, New Zealand, Philippines PICCS, and Switzerland Inventories.

STORAGE AND HANDLING:

Containers should be kept tightly closed. For bulk storage, stainless steel tanks are recommended. Recertification is recommended one year from the date of manufacture provided the material has been stored properly and drums have remained unopened. Do not store in high heat areas, or near fire or open flame. Use proper bonding and grounding during liquid transfer as described in National Fire Protection Association document NFPA 77. Octowet should be stored at temperatures 40 – 90 degrees Fahrenheit.

03/16;05/15;08/14;04/14;10/12;07/11;03/07;03/06;0300

The information provided herein is believed to be reliable; however, no guarantees are made or liability assumed. Tiarco Chemical makes no claims or warranties concerning the suitability of the product for a particular use or purpose.