



## AVALUBE FG TECHNICAL DATA SHEET

### DESCRIPTION

Avalube FG is a premium quality food grade lubricant designed for lubrication of application in food industry. It is registered with NSF as H-1 grade grease, Kosher and Halal approved. Avalube FG is highly water-resistant, minimizing loss of lubricant that sometimes occurs when machines are washed. This makes it suitable for use in food processing plants where incidental contact with food is possible. This grease has high load bearing capabilities, rust prevention additives and good water resistance properties.

### BENEFITS

- Resists pound-out, wash out.
- Water resistant, superior capability to stay in place.
- Extreme pressure and rust protection.

### APPLICATIONS

Avalube FG is very versatile and may be used to lubricate bearings, bushings, slides, rollers and cam followers.

ASTM#	Typical Characteristics
	NLGI Grade 2
	NSF Registration H-1
	Color White
	Thickener Type Aluminum Complex
D-217	Penetration (Worked) 265 – 285
D-2265	Dropping Point, °F (°C) >500 (>260)
D-445	Viscosity (Base Oil) cSt @ 40°C, @ 100°C 458, 32
D-2596	Four Ball EP, Weld Point, kg 400
D-2509	Timken OK Load, lb 50
D-1264	Water Washout, % Loss < 3
	Operating range, °F 0 - 350
<b>Packaging</b>	400 # Drum, 35 # Pail

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.