





# GMCraft 60

## Weather-Resistive Barriers



## Product Data Sheet

### Product Description

**GMCraft** is asphalt saturated building paper, and is also described as a weather-resistive barrier, or moisture barrier in building codes. It is designed for installation behind stucco and other exterior wall claddings as a “secondary weather barrier”. **GMCraft** contributes to the prevention of internal wall damage due to exterior moisture penetration or interior condensation.

### Products Standards

**GMCraft 60** is a “weather-restrictive barrier” as described in Section 1404.2 of the 2000 International Building Code® (IBC) and also qualifies as a “weather-resistive sheathing paper” as described in Section R703 of the 2000 International Residential Code™ (IRC).

**GMCraft 60** exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade “D”, Style 2, and complies with Section 1402.1 of the 1997 Uniform Building (and subsequent UBC and CBC editions).

**GMCraft 60** has maintained ICC (formerly IBCO) Evaluation Reports, since October of 2000 and satisfies the test criteria for weather-resistive barriers (AC 38) dated July 2000. The outer surface is boldly printed with appropriate ICC ESR identification information. The current ESR 2376 is dated May 1, 2010.

**GMCraft 60** is evaluated by ongoing testing to insure that it meets or exceeds industry standards (including ASTM D-779-03, ASTM D-828). March 29, 2010 test results from an ICC Certified Testing Laboratory are listed below:

<b>GMCraft 60</b>	Test Method	Test Results
Water Vapor Transmission	ASTM E-96-00	<b><u>90 grams Pass</u></b>
Water Resistance	ASTM D-779	<b><u>Exceeds 60 minutes</u></b>
Tensile Strength	ASTM D-828	<b><u>MD 60 lb-f/in</u></b> <b><u>CD 44 lb-f/in</u></b>

### Physical Description

GMCraft 60 *Single* cover 240 SF (Roll Size: 40” x 72 lineal feet)  
 GMCraft 60 *Double* covers 162 SF (Roll Size: 40” x 49 lineal feet – 2 layers)

**Manufactured by**  
**GMC Roofing & Building Paper Products, INC.**  
 6400 Zerker Road, Shafter, CA. 93263  
 (661) 399 4324



# GMCraft 60/30 Weather-Resistive Barriers



## Product Data Sheet

**GMCraft** is asphalt saturated building paper, which is also described as a weather-resistive barrier, or moisture barrier. It is designed for installation behind stucco, and other exterior wall claddings as a “secondary weather barrier”. **GMCraft** provides the needed protection from internal wall damage due to moisture leakage and condensation.

**GMCraft** is a “weather-restrictive barrier” as described in Section 1404.2 of the 2000 International Building Code® (IBC) and also qualifies as a “weather-resistive sheathing paper” as described in Section R703 of the 2000 International Residential Code™ (IRC).

**GMCraft** exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade “D”, Style 2, in accordance with Section 1402.1 of the 1997 Uniform Building Code (and subsequent editions).

**GMCraft** has maintained an ICC (formerly IBCO) Evaluation Report, No. 5924 since October of 2000 and satisfies test criteria for weather-resistive barriers (AC 38) dated July 2000. **GMCraft** maintains ongoing testing to insure that it meets or exceeds industry standards (including ASTM D-779-03, ASTM D-828, and ASTM E-96-03) and has applied for ongoing approvals from ICC ES.

**GMCraft is announcing the introduction of packaged combination of 1 layer of 60 minute and 1 layer 30 minute weather barrier to be known as “GMCraft 60/30 Double”. (See test results below). This product provides superior protection at an affordable price. Cumulative results will be greater than sum total of liners!**

### Test Results

<b>GMCraft 60/30</b>		Test Results	Fed Spec. UU B 790a
Water Vapor Transmission	ASTM E-96-00	<b>200 perms</b>	35 perms (min)
Water Resistance	ASTM D-779	<b><u>1 hour+</u></b> ➤ <b><u>.5 hours+</u></b> <b>total &gt; 1.5 hrs +</b>	10 minutes
Tensile Strength	ASTM D-828	<b>MD comb.</b> <b>90+ lb-f/in</b> <b>CD comb.</b> <b>64+ lb-f/in</b>	MD 20lb.-f/in  CD 20lb.-f/in

041807X368

### Physical Description

**GMCraft 60/30 (1 layer each - not glued)**  
**GMCraft 60 covering 162 SF and is 40” x 49 lineal feet.**  
**GMCraft 30 covering 162 SF and is 40” x 49 lineal feet.**

*Manufactured by*  
**GMC Roofing & Building Paper Products, INC.**  
**6400 Zerker Road, Shafter, CA. 93263**  
**(661) 399 4324**



# GMCraft 10 Weather-Resistive Barriers



## Product Data Sheet

### Product Description

**GMCraft** is asphalt saturated building paper, which is also described as a weather-resistive barrier, or moisture barrier. It is designed for installation behind stucco, and other exterior wall claddings as a “secondary weather barrier”. **GMCraft** provides the needed protection from internal wall damage due to moisture leakage and condensation.

### Products Standards

**GMCraft 10** is a “weather-restrictive barrier” as described in Section 1404.2 of the 2000 International Building Code® (IBC) and also qualifies as a “weather-resistive sheathing paper” as described in Section R703 of the 2000 International Residential Code™ (IRC) - (and subsequent editions of these codes).

**GMCraft 10** exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade “D”, Style 2, in accordance with Section 1402.1 of the 1997 Uniform Building Code (and subsequent editions).

**GMCraft 10** has maintained an ICC (formerly IBCO) Evaluation Report, since October of 2000 and satisfies test criteria for weather-resistive barriers (AC 38) dated July 2000. It currently has an approval until 2017 and **ESR # is 2376 meets 2012**, 2009 and 2006 International Building Code Requirements.

**GMCraft 10** maintains ongoing testing to insure that it meets or exceeds industry standards (including ASTM D-779-03, ASTM D-828, and ASTM E-96-03). See typical results below.

### Test Results

<b>GMCraft 10</b>	Test Method	Test Results	Industry Standard
Water Vapor Transmission	ASTM E-96-00	<b>38 grams (+)</b>	35 grams (min)
Water Resistance	ASTM D-779	<b><u>Exceeds 20 minutes</u></b>	10 minutes
Tensile Strength	ASTM D-828	<b>MD 45 lb-f/in CD 21 lb-f/in</b>	MD 20lb.-f/in CD 20lb.-f/in

### Physical Description

*GMCraft 10 Single covers 324 SF and is 40” x 98 lineal feet.  
GMCraft 10 Double covers 162 SF and is 40” x 49 lineal feet.*

**Manufactured by  
GMC Roofing & Building Paper Products, INC.  
6400 Zerker Road, Shafter, CA. 93263  
(661) 399 4324**