


ANCHOR SHACKLES

- Meet or Exceed FED SPEC RR-C-271 • Hot Dip Galvanized to ASTM A153
- Meet ASME B30.26 Requirements • Proof Load at 2 times the Working Load Limit
- Forged Carbon or Alloy Steel Body • Ultimate Load at 6 times the Working Load Limit

Screw Pin Anchor Shackles


Ideal for applications where frequent pin removal is needed. Forged, Quenched and Tempered Galvanized Alloy Steel Body and Pins.



Part Number	Size (in.)	WLL (ton)	Pin Diameter (in.)	A (in)	B (in)	C (in)
8058203	1/4	3/4	5/16	3/4	1 1/8	7/16
8058303	5/16	1	3/8	13/16	1 1/4	1/2
8058403	3/8	2	7/16	15/16	1 9/16	5/8
8058503	1/2	3 1/3	5/8	1 3/16	1 7/8	13/16
8058603	5/8	5	3/4	1 1/2	2 7/16	1 1/16
8058703	3/4	7	7/8	1 3/4	2 7/8	1 1/4
8058803	7/8	9 1/2	1	2	3 5/16	1 1/2
8058903	1	12 1/2	1 1/8	2 5/16	3 3/4	1 11/16
8059003	1 1/4	18	1 3/8	2 7/8	4 11/16	2 3/16
8059103	1 1/2	30	1 5/8	3 3/8	5 3/4	2 3/8
8059403	1 3/4	40	2	4 1/2	7	2 7/8
8059503	2	50	2 1/4	5 1/4	7 3/4	3 1/4

Safety Pin Anchor Shackles

Complete with bolt, nut and cotter pin; Overhead lifting applications where pin removal is minimal. Forged, Quenched and Tempered Galvanized Carbon Steel Body and Alloy Pins.



Part Number	Size (in.)	WLL (tons)	Pin Diameter (in.)	A (in)	B (in)	C (in)
8063105	1/4	1/2	5/16	3/4	1 1/8	7/16
8063205	5/16	3/4	3/8	13/16	1 1/4	1/2
8063305	3/8	1	7/16	15/16	1 7/16	5/8
8063505	1/2	2	5/8	1 3/16	1 7/8	13/16
8063605	5/8	3 1/4	3/4	1 1/2	2 7/16	1 1/16
8063705	3/4	4 3/4	7/8	1 3/4	2 7/8	1 1/4
8063805	7/8	6 1/2	1	2	3 5/16	1 7/16
8063905	1	8 1/2	1 1/8	2 5/16	3 3/4	1 11/16
8064105	1 1/4	12	1 3/8	2 7/8	4 11/16	2 3/16
8064305	1 1/2	17	1 5/8	3 3/8	5 3/4	2 3/8
8064405	1 3/4	25	2	4 1/2	7	2 7/8
8064505	2	35	2 1/4	5 1/4	7 3/4	3 1/4