

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	Monticello
-------------	---------------	-------------------

TECHNICAL CHARACTERISTICS			
Available Formats:	18x18, 13x13, 12x24, 2x2 Mosaic 13x13 Sheet, 3x13 Floor Bullnose		
Style Description:	Porcelain	Glaze Application Method:	Inkjet
Visual Characteristics:	Rapolano Look	Number of Faces/Screens:	Random
Thickness in mm:	10.5	Number of Punches/Molds:	1 (Flat)
Modular Suitability:	No	Body Type:	PORCELAIN (>.5%)
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	0	Surface Type:	Matte & Textured
Rectified:		Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<0.5%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.61
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300N
Frost Resistant:	YES	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class 5		

PACKING INFORMATION - 18x18 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	15.27	Pieces per Carton:	7
SqFt per Pallet:	794.04	Pounds per Carton:	61.08
Boxes per Pallet:	52	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".