

4184 E. Conant St. Long Beach, CA 90808 Tel. 888-900-1002 Fax. 310-900-1088 www.turboairinc.net

— · ·	
Droioct	
Project	
,	

Item # :

Model # :

Qty :

Approval :

Condensing Unit

Model : TS035XR404A2



____ FEATURES / BENEFITS ____

- Blue anti-corrosion-fin increases the life span of the coil.
- Seamless inner groove copper tube increases the heat exchange rate by reducing the space between the fin and copper tube.
- Highest quality compressor in the world.



- Head pressure control stabilizes the freezing of liquid line, minimizes formation of flash gas to increase efficiency of the system, and prevents compressor damage by controlling high pressure.
- Experienced engineers have designed the system for maximum sfficiency.
- Fan Blades : Specifically matched with motors and coil for maximum air movement and cooling.

- Control box is designed for easy installation.
- Low pressure control is adjustable.
- All the parts are compliant with industry standards and interchangeale with readily available parts.
- Wiring : Easily accessible. Compressor comes with a wiring harness that is manufactured with connections that will not come loose with vibration.
- Control box and service valves are located outside for easy service.
- Base : Heavy duty steel. Legs are 2-1/6" tall
- Cabinet : Prepainted with galvanized body. Protects against corrosion.
- All products carry UL, cUL, ISO 9001 approvals.



Condensing Unit

Model : TS035XR404A2

PERFORMANCE CHART

	0°F(SST)	-10°F	-20°F	-25°F	-30°F	-35°F	-40°F
90'F(AMBIENT)	19800	16490	14910	13420	12000	10710	8530
95'F	19040	15860	14340	12900	11540	10300	8200
100'F	18280	15230	13770	12380	11080	9890	7870
110'F	16760	13960	11350	10160	9060	8140	7220

SPECIFICATION

Compressor	ZF11K4E-PFV			
Line Size	1/2" Liquid 7/8" Suction			
Receiver 90%	13			
Fan Data	2Fan (2010CFM)			
Dimensions	28.27(D) x 38.5W) x 22.87(H)			
Net Weight	257 Lbs			
Power Supply	208-230/1ph/60hz			
Compressor Amp	20.7			
MCA	27.8			
MOPD	45			

Design and specifications subject to change without notice

- Suction and discharge vibration eliminators with Discus compressors.
- Oil failure switch with Discus compressors.
- To prevent damage of compressor that resulted from liquid-compression, accumulator was installed in this units.


IRadiance

• To improve efficiency, installed oil separator

WARRANTY : 1 Year Compressor Warranty (4 Year extended warranty available)
1 Year Fan Motor and Parts Warranty


PLAN VIEW

(unit : inch)



(GERMAN

KNIFE)



Toll Free : 888-900-1002

GREEN WORLD Turbo air



I YEAR

(UL)

_د(۳۲