



## SHEET METAL PRODUCTS

COMMERCIAL GRADE

CONICAL FLANGE & GASKET

### FLANGE & GASKET COLLAR - MODEL FLCSOC, FLCSOC-D1 & FLCSOCD3

Expedite field installations with Peppertree Model FLCSOC quality Flange and Gasket Fittings (with or without damper). All FLCSOC's are fabricated with a seamless 1" Mounting Flange and a bead for non-slip positioning of draw bands or gear clamps. Our damper blades are fabricated with quality hardware including stamped handles, spring loaded & solid bearings and locking adjustable wing nuts. We can also provide heavy duty handles and stand-off regulators with full locking quadrants for insulated ductwork.



Photo FLCSOCD3

FLCSOCD	FLCSOCD1	FLCSOCD3
<ul style="list-style-type: none"> <li>• 1" Flange</li> <li>• 1/8" PE Foam Gasket</li> <li>• Damper &amp; hardware</li> <li>• 7.5" overall body length</li> <li>• Beaded sleeve</li> <li>• Galvanized steel 26/24ga</li> <li>• Aluminum 3003</li> <li>• 04" to 20" diameters</li> </ul>	<ul style="list-style-type: none"> <li>• 1" Flange</li> <li>• 1/8" PE Foam Gasket</li> <li>• 2" Extended Handle</li> <li>• 7.5" overall body length</li> <li>• Beaded sleeve</li> <li>• Galvanized steel 26/24ga</li> <li>• Aluminum 3003</li> <li>• 04" to 20" diameters</li> </ul>	<ul style="list-style-type: none"> <li>• 1" Flange</li> <li>• 1/8" PE Foam Gasket</li> <li>• 2" stand-off</li> <li>• Locking quadrant</li> <li>• 3/8" square rod</li> <li>• Low leakage</li> <li>• Nylon bushings</li> <li>• 10" overall body length</li> <li>• Galvanized steel 26/24ga</li> <li>• Aluminum 3003</li> <li>• 04" to 20" diameters</li> </ul>

These products simplify installation and enhance design efficiencies. Submittal data is available on our website. We also offer a variety of fittings including Spin-on Collars and Connecting collars.