



SLOKY Preset Torque Screwdriver—LT Combo Sets



STS-TX-LT-S1



STS-IP-LT-S1

Description

Product:	SLOKY Preset Torque Screwdriver—LT Combo Sets
Models:	STS-TX-LT-S1 for TORX, STS-IP-LT-S1 for TORX-PLUS
Content:	13 PCS/Set, Sizes—TX6, TX7, TX8, TX9, TX10, TX15 1) 1 PC of LT Handle 2) 6 PCS of Adapters, 1 PC of Each Size, 3) 6 PCS of 1" Bit for TORX/TORX-PLUS, 1 PC of Each Size
Packaging:	Hinged Open Top Plastic Box
Dimension:	4 3/4"X4 1/2"X1 1/2" (LWH)
Weight:	0.63 lbs

Specifications

Bits:	High Alloy Steel, Hardness 58°-60°, Color Marked, 1/4" Hex Shank, 1" & 2" (L)
Handle:	LT Handle, 2 3/4" X 3/4" X 1 1/2" (LWH)
Adapters:	Preset Torque, Color Marked, Magnetized, 1/4" Hex Shank , 1 1/2" (L), 1/2" (Dia.)

Preset Torque:

TX6	■	0.6 Nm/5.3 In-lb	TX7	■	0.9 Nm/8.0 In-lb
TX8	■	1.2 Nm/10.6 In-lb	TX9	■	1.4 Nm/12.4 In-lb
TX10	■	2.0 Nm/17.7 In-lb	TX15	■	3.0 Nm/26.6 In-lb

Max. Actions:	20,000 Times in Life-Time
Allowance:	±10%
Patents:	US8549963, US201202040734
Applications:	Cutting Tools/Machining, Parts Assembling/Electronics & Aerospace






















SLOKY Preset Torque Screwdriver

Features

Replaceable:	All three types of handle are replaceable. Any adapter fits any type of handle
Color Marks:	All the adapters and bits are color marked for easy pairing
Accuracy:	Patented adaptor ensures the preset torque is applied, with the tolerance of $\pm 10\%$
Operation:	Adapter will automatically release the connection with handle when the preset torque is reached and ends the screw tightening operation
Signaling:	Exceeding turns will only generate signal sound, no more torque is applied

Configuration

 LT Handle	 0.6Nm/5.3 In-lb	 TX/IP 6	
	 0.9Nm/8.0 In-lb	 TX/IP 7	
	 1.2Nm/10.6 In-lb	 TX/IP 8	
	 1.4Nm/12.4 In-lb	 TX/IP 9	
	 2.0Nm/17.7 In-lb	 TX/IP 10	
	 3.0Nm/26.6 In-lb	 TX/IP 15	
	 5.0Nm/44.3 In-lb	 TX/IP 20	
	 5.5Nm/48.7 In-lb	 TX/IP 25	
	 HD Handle		
	 ST Handle		

Notes

Warning:	Adapters are designed for manual operations, not suitable for use of power tools
Compatibility:	TORX Bits can be used on TORX-PLUS screws, but not vice versa
Trade Mark:	TORX & TORX-PLUS are the registered trademarks of Camcar Textron (USA)