

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

COTTO

## TECHNICAL CHARACTERISTICS

|   |  |                           |                        |
|---|--|---------------------------|------------------------|
| Available Formats:                        | 20x20 Available in an indoor/outdoor finish; 3x20 Bullnose available in indoor finish only |                           |                        |
| Style Description:                        | Cotto  | Glaze Application Method: | HDIT Inkjet            |
| Visual Characteristics:                   | Cotto  | Number of Faces/Screens:  | N/A                    |
| Thickness in mm:                          | 10   | Number of Punches/Molds:  | 1                      |
| Modular Suitability:                      | No   | Body Type:                | Porcelain (< .5%)      |
| Application:                              | Residential/Commercial   | Color Body Unglazed:      | No                     |
| Recycled Content:<br>Post or Pre Customer | N/A  | Surface Type:             | Matte & Rough Textured |
| Rectified:                                | No   | Recommended Grout Joint:  | No less than 3/16"     |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |       |  |        |
|------------------------------|-------|--|--------|
| Water Absorption:            | < .5% | Static COF:                              | N/A    |
| Shade Variation (1, 2, 3, 4) | V2    | Dynamic COF:                             | N/A    |
| Scratch Hardness (MOHS)      | 7+    | Breaking Strength:                       | >1300N |
| Frost Resistant:             | Yes   | Thermal Shock Resistance:                | Yes    |
| PEI/Abrasion Resistance:     | IV    | Deep Abrasion Test <175mm <sup>2</sup> : | N/A    |
| Chemical Resistance:         | N/A   |  |        |

## PACKING INFORMATION

|                        |        |                     |          |
|------------------------|--------|---------------------|----------|
| SqFt per Carton:       | 13.45  | Pieces per Carton:  | 5        |
| SqFt per Pallet:       | 484.20 | Pounds per SqFt:    | 5.62 lbs |
| Boxes per Pallet:      | 36     | SqFt per Container: | N/A      |
| Pallets per Container: | N/A    |                     |          |

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".