

SAFETY DATA SHEET

J&B PART NUMBER

9158

1. Identification

Product identifier

Disc Brake Quiet

Other means of identification

Product code 05017

Recommended use Apply to brakes to decrease noise

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name

CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information

215-674-4300

Technical

800-521-3168

Assistance

Customer Service

800-272-4620

24-Hour Emergency

800-424-9300 (US)

(CHEMTREC)

703-527-3887 (International) www.crcindustries.com

Website

2. Hazard(s) identification

| Physical hazards | Flammable aerosols | Category 1 |
|------------------|-----------------------------------|---------------|
| | Gases under pressure | Liquefied gas |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2 |
| | Aspiration hazard | Category 1 |

Environmental hazards Hazardous to the aquatic environment. Category 1 Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

Precautionary statement Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves. Wear eye/face protection. Avoid release to the environment.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting, If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Collect spillage.

Material name: Disc Brake Quiet

Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

3. Composition/information on ingredients

| lixtures | ing | | A receive |
|---|--------------------------|------------|-----------|
| Chemical name | Common name and synonyms | CAS number | % |
| n-Hexane | | 110-54-3 | 20 - 30 |
| Propane | | 74-98-6 | 20 - 30 |
| Acetone | | 67-64-1 | 10 - 20 |
| n-Butane | | 106-97-8 | 10 - 20 |
| Ethyl acetate | | 141-78-6 | 3 - 5 |
| Solvent naphtha (petroleum), light aliph. | | 64742-89-8 | 3 - 5 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

protect themselves.

4. First-aid measures

| 4. First-aid measures | |
|--|--|
| Inhalation | Move to fresh air. If breathing is difficult, trained personnel should give oxygen. Get medical attention immediately. |
| Skin contact | Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to |

5. Fire-fighting measures

| 5. Fire-righting measures | |
|---|---|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire-fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. |
| General fire hazards | Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. |

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Many vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Disc Brake Quiet

05017 Version #: 01 Issue date: 05-30-2015

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

| cupational exposure limits | | | |
|--|------------------------------------|----------------|--|
| US. OSHA Table Z-1 Limits for Air Components | Contaminants (29 CFR 1910. Type | 1000) Value | |
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 | |
| | | 1000 ppm | |
| Ethyl acetate (CAS | PEL | 1400 mg/m3 | |
| 141-78-6) | | EL CONTRACTOR | |
| (0.0.4.0.5.4.0) | | 400 ppm | |
| n-Hexane (CAS 110-54-3) | PEL | 1800 mg/m3 | |
| 2010-110-1 | | 500 ppm | |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m3 | |
| | | 1000 ppm | |
| US. ACGIH Threshold Limit Values | • | | 1,7 m grid 1944 |
| Components | Type | Value | |
| Acetone (CAS 67-64-1) | STEL | 750 ppm | 12 °. m |
| | TWA | 500 ppm | |
| Ethyl acetate (CAS 141-78-6) | TWA | 400 ppm | |
| n-Butane (CAS 106-97-8) | STEL | 1000 ppm | |
| n-Hexane (CAS 110-54-3) | TWA | 50 ppm | |
| US. NIOSH: Pocket Guide to Chem | ical Hazards | | |
| Components | Туре | Value | |
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 | The state of the s |
| | | 250 ppm | |
| Ethyl acetate (CAS 141-78-6) | TWA | 1400 mg/m3 | re in largery you comment |
| , | | 400 ppm | the state of the s |
| n-Butane (CAS 106-97-8) | TWA | 1900 mg/m3 | |
| , | | 800 ppm | |
| n-Hexane (CAS 110-54-3) | TWA | 180 mg/m3 | |
| , | | 50 ppm | |

Material name: Disc Brake Quiet

SDS US

05017 Version #: 01 Issue date: 05-30-2015

US. NIOSH: Pocket Guide to Chemical Hazards

Components Type Value Propane (CAS 74-98-6) TWA 1800 mg/m3

Biological limit values

| ACGIH | Biological | Exposure | Indices |
|--------------|------------|----------|---------|
|--------------|------------|----------|---------|

| Components | Value | Determinant | Specimen | Sampling Time | |
|-------------------------|----------|-----------------------------|----------|---------------|--|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * | |
| n-Hexane (CAS 110-54-3) | 0.4 mg/l | 2,5-Hexanedio n, without | Urine | * | |
| | | hydrolysis | | | |

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

1000 ppm

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation. or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile.

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Aerosol. Color Red. Odor Solvent. Odor threshold Not available. ΡH Not available.

Melting point/freezing point

-138.5 °F (-94.7 °C) estimated

Initial boiling point and boiling

> 100 °F (> 37.8 °C)

range

Flash point

< 20 °F (< -6.7 °C) Closed Cup

Evaporation rate Moderate. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

1.1 % estimated

(%)

Flammability limit - upper

12.8 % estimated

(%)

Material name: Disc Brake Quiet

SDS US 05017 Version #: 01 Issue date: 05-30-2015

Vapor pressure 3293.6 hPa estimated

Vapor densityNot available.Relative density0.76 - 0.78Solubility (water)Insoluble.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature 437 °F (225 °C) estimated

Decomposition temperatureNot available.Viscosity (kinematic)Not available.Percent volatileNot available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Alkalies. Strong oxidizing agents. Strong reducing agents. Nitrates. Fluorine. Chlorine.

Chloroform. Potassium t-butoxide.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Teet Regulte

vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Species

| | opooloo | Tool Results | |
|------------------|---------|--|-------------|
| Disc Brake Quiet | | | 4 - 19 - 1 |
| Acute | | | |
| Dermal | | | #1 W 1130.v |
| LD50 | Rabbit | 3652 mg/kg estimated | |
| Inhalation | | to the Date of the State of St | |
| LC50 | Rat | 3323 mg/l, 4 Hours estimat | ed |
| Oral | | | |
| LD50 | Rat | 19482 mg/kg estimated | |
| | | | |

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Product

Causes serious eye irritation.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Material name: Disc Brake Quiet

SDS US

05017 Version #: 01 Issue date: 05-30-2015

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting,

may cause chemical pneumonia, pulmonary injury or death.

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

| otoxicity | Toxic to a | equatic life with long lasting effects. | -14h - 1 | Activity & Society |
|--------------------------|------------|--|--------------------------|------------------------|
| Product | | Species | Test Results | And the moral |
| Disc Brake Quiet | | | 3 | as allidete or |
| Aquatic | | | | |
| Crustacea | EC50 | Daphnia | 80532.2656 mg/l, 48 | hours estimated |
| Fish | LC50 | Fish | 205.9306 mg/l, 96 ho | ours estimated |
| Components | | Species | Test Results | |
| Acetone (CAS 67-64-1) | | - dain't every built to a horself extend to | JI 1967 | er er zedagele" |
| Aquatic | | | eigh eigh | comments arment |
| Crustacea | EC50 | Water flea (Daphnia magna) | 10294 - 17704 mg/l, | 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 | hours |
| Ethyl acetate (CAS 141-7 | 8-6) | | 10 - 0 - 10 - 18 | My Think I'm |
| Aquatic Fish | LC50 | Indian catfish (Heteropneustes fossilis) | 200.32 - 225.42 mg/l | bull the public tracks |
| n-Hexane (CAS 110-54-3) |) | | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas | i) 2.101 - 2.981 mg/l, 9 | 6 hours |

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

| Partition coefficient n-octanol | / water | (log Kow) | 1 |
|---------------------------------|---------|-----------|---|
|---------------------------------|---------|-----------|---|

| Acetone | -0.24 |
|---------------|-----------|
| Ethyl acetate | 0.73 |
| n-Butane | 2.89 |
| n-Hexane | 3.9 |
| Propane | 2.36 |

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code

D001: Waste Flammable material with a flash point <140 F

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

05017 Version #: 01 Issue date: 05-30-2015

UN proper shipping name Aerosols, flammable, Limited Quantity, MARINE POLLUTANT (Hexanes)

Material name: Disc Brake Quiet

State of the second of the second of the second second of the second second of the second sec

SDS US

6/9

Transport hazard class(es)

Class 2.1
Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Environmental hazards Yes. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only Allowed.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, LIMITED QUANTITY, MARINE POLLUTANT

Transport hazard class(es)

Class 2

Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes. EmS F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

n-Hexane (CAS 110-54-3)

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.
Ethyl acetate (CAS 141-78-6) Listed.
n-Hexane (CAS 110-54-3) Listed.

CERCLA Hazardous Substances: Reportable quantity

Acetone (CAS 67-64-1) 5000 LBS Ethyl acetate (CAS 141-78-6) 5000 LBS n-Hexane (CAS 110-54-3) 5000 LBS

Material name: Disc Brake Quiet

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)

6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)

35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

6532

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Hazard categories Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes

Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1)

n-Butane (CAS 106-97-8)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

n-Hexane (CAS 110-54-3)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Ethyl acetate (CAS 141-78-6)

n-Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Ethyl acetate (CAS 141-78-6)

n-Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Ethyl acetate (CAS 141-78-6)

n-Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Ethyl acetate (CAS 141-78-6)

n-Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65); This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

Not determined

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products Not regulated

> VOC content (CA) 59.5 %

> VOC content (OTC) 59.5 %

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-30-2015 Prepared by Allison Cho

Version # 01

Further information Not available. **HMIS®** ratings Health: 1 Flammability: 4

Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1 Flammability: 4

Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

Material name: Disc Brake Quiet SDS US