

HITACHI
Inspire the Next

65 inch FHD Interactive
Flat Panel Display



*All images are simulated.

- **65 inch Full HD Resolution Panel**

All-in-one solution with 65 inch Full HD panel.

- **Up to 10 point of touch (simultaneous)**

Ideal function for class rooms.

You can write from both right and left sides.

- **Stereo speakers (20W total)**

20W stereo speakers facilitate to deliver the sound to your audience directly.

- **Front HDMI and USB inputs**

Simply plug in your computer with HDMI and USB for touch control and you are ready to go.

- **Both Windows® and Mac OS® compatible**

- **More convenient features are available, including**

LAN port for control, OPS slot, magnetic stylus pens.

Technical Specifications

LED PANEL	
Diagonal size	64.53" / 163.9(cm)
Display Resolution (Max.)	1,920 x 1,080 (FHD)
Brightness (average)	350 cd/m ²
Viewing Angle	H: 176° / V: 176°
Contrast ratio	5000:1 (Typ.)
Supported Colors	16.7M colors (8bit)
Response Time	6.5ms (Gray to Gray)
Display Frame Rate	60Hz (Actual)
Installation	Landscape Orientation

TOUCH	
Detect area	1428.5(H) x 803.5(V) mm / 56.24"(H) x 31.63"(V)
Detection method	Infrared blocking Detection Method
Touch tool	Hand or other solid object
Accuracy	±2mm
Response time	< 12ms
Available Touch Point	10 Points
Operating Systems	Windows7, 8, 10/ Mac OS 10.10-10.12
PC connector	USB

SIGNAL CONNECTIVITY	
Video Input	HDMI x 2 (Rear x1, Only for inside OPS x1), Display Port x1, VGA x1
Audio	RCA Speaker Out(R/L), Stereo Mini Lineout, Stereo Mini Input
Communication Port	RJ45(LAN), RS-232C(D-sub 9-pin), USB-B (Only for touch control) x1 (Either front or rear port is workable)
Front Input	HDMI x1(as specified in "Video Input"), USB-B(only for touch control as specified in "Communication Port")x1, USB-A x1

MECHANICAL	
Dimensions Landscape	1506 x 902 x 92 mm
Weight (Mass)	44.3 kg (97.6 lbs)
VESA mount	400 x 200 (mm), M8 Screw
Front Glass	Tempered Glass 4.0t (Anti-glare Type)

ELECTRICAL	
Power Requirement	100 - 240V AC, 50/60 Hz
Power Consumption	Max. 185W
Power Consumption (Standby)	< 0.5W
Speaker Output	10W + 10W Stereo (8-ohms)

ENVIRONMENTAL	
Operating Temperature	0 ~ 40 °C (32 ~ 104 °F)
Storage Temperature	- 20 ~ 60 °C (-4 ~ 140 °F)
Operating Humidity	20% to 80% RH (no condensation)

OSD FUNCTIONS	
OSD Language Function	English / Français / Deutsch / Spanish / Portugues / Italiano / Danish / Swedish / Norwegian / Suomi / Russian / Polish / Turkish / Hungarian / Chesky / Korean / Dutch / Vietnamese
OSD Key Lock Function	Support

ACCESSORIES	
Magnetic stylus pen x 2 , Remote controller, HDMI Cable, USB Cable, Power Cable, CD (User Manual, Installation Manual, Touch driver)	

CERTIFICATIONS	
QAS, RCM, CB, RoHS	



/hitachiDPSAustralia



@HitachiAU_DPS



USB for TOUCH



RS232C



HDMI 2



HDMI 1



DISPLAY PORT



VGA INPUT



PC AUDIO IN



AUDIO LINE OUT



R SPEAKER OUT(8Ω)



L SPEAKER OUT(8Ω)



AC IN
100-240 V-
50/60 Hz

- Design and specifications are subject to change without notice.
- Microsoft, Encarta, MSN, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Mac OS® is registered trademarks of Apple Inc.
- HDMI, High-Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and/or other countries.
- All other trademarks and registered trademarks are the property of their respective owners in the United States and/or other countries.

HITACHI DIGITAL PRESENTATION SOLUTIONS
Hitachi Australia Pty. Ltd.
Tel: 1 800 HITACHI www.hitachi.com.au/dps