



SUBMITTAL DATA
SHEET METAL FITTINGS

**Flange & Gasket
CONICALS**

Conical Fittings

(Tolerance on all sizes +/- 1/8")

Nom. Dia.	Sleeve O.D.	Cone I.D	Length No Damper	Length With Damper	Flange O.D.
4"	3.875	5.75	7.5	10"	8
6"	5.875	7.75	7.5	10"	10
8"	7.875	9.75	7.5	10"	12
10"	9.875	11.75	7.5	10"	14
12"	11.875	13.75	7.5	10"	16
14"	13.875	15.75	7.5	10"	18
16"	15.875	17.75	7.5	10"	20
18"	17.875	19.75	7.5	10"	22
20"	19.875	21.75	7.5	10"	24

Flange – 1" wide, galvanized steel

Gasket - 1/8" PE Foam, PSA

Fitting Model

- FLCSOC No Damper
- FLCSOCD Standard Damper – Spring End Bearing with Handle and Wingnut
- FLCSOCD1 2" Damper Handle Extension
- FLCSOCD3 2" Buildout – 3/8" square shaft, Nylon End Bearings and Locking Handle

Standard Construction

- Galvanized Steel, 26 Ga. thru 12" Dia., 24 Ga. on 14" Dia. and above

Gauge Options

- 24 Gauge
- 22 Gauge
- 20 Gauge
- Other _____

Material Options

- Galvanized Steel
- Aluminum
- Stainless Steel
- Other _____