

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

WOOD SQUARED

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Rustic Wood	Glaze Application Method:	Rotocolor
Visual Characteristics:	Wide Wood Mix	Number of Faces/Screens:	N/A
Thickness in mm:	N/A	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	Color Body
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: .6 Dry: 0.6
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	N/A
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm ² :	Meets
Chemical Resistance:	Meets		

PACKING INFORMATION - 24x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	6
SqFt per Pallet:	465.20	Pounds per Carton:	54.66 Lbs
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".