



Touch Probe TC60



High-Speed touch probe with latest BRC radio transmission technology and multidirectional measuring mechanism

- Perfect for large 5-axis machines where line of sight between probe and receiver is blocked or intermittent
- Detection of workpiece position
- Correction of workpiece orientation
- Thermal compensation of the machine tool
- Contour measurement



- Measuring speed up to 3 m/min
- Precise, non-lobing touch characteristics
- No-wear, optoelectronic measuring mechanism
- · Easy pairing procedure between probe and receiver
- Use of up to 6 measuring systems with one receiver
- · Extended battery life
- · Precise measurement even with coolant
- · Proven and robust design



BRC Radio Technology


Sequential use of up to 6 measuring systems with one radio receiver.

Technical data


Protection class	IP68
Approach directions	±X, ±Y, -Z
Measuring force in XY Z	2 N* 7 N
Max. deflection XY Z	± 15° 10 mm
Max. acceleration	50 m/s ²
Repeatability	0,3 μm 2σ
Max. probing speed	3 m/min
Mass	925 g
Signal transmission	Radio (BRC Technology)
Frequency band	2,4000 - 2,4835 GHz
Transmission power	O dBM
Operating range	15 m
Battery (2 pieces)	Saft Lithium LS 14500 (AA, 3,6V) 2600 mAh
Tool holder	BTH 50 (HSK, SK, BT, VDI,)
Storage/Operating temperature	-20 °C +70 °C +5 °C +50 °C
* Stylus L= 50 mm	



BRC radio system – extremely fast & robust



Non-lobing touch characteristics



Modern and precise measuring mechanism with optoelectronic signal generation



Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 Fax: +44 1543 251746 E-Mail: info@blum-novotest.co.uk **Blum LMT, Inc.** 4144 Olympic Boulevard Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com