

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Martha's Vineyard

## TECHNICAL CHARACTERISTICS

Available Formats:	12x48, 8x48		
Style Description:	White Washed Wood	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	8mm	Number of Punches/Molds:	2
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	59% pre consumer; 6% post	Surface Type:	Matte
Rectified:	Rectified	Recommended Grout Joint:	1/8"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	>450LBF
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	Yes		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.59	Pieces per Carton:	6
SqFt per Pallet:	498.88	Pounds per Carton:	54.72
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".