

FUSO – A Daimler Group Brand



2017

FE130

Efficiency that delivers.



MITSUBISHI FUSO TRUCK OF AMERICA, INC.

FE130

SPECIFICATIONS

Rugged and responsive, the FUSO FE130 will change the way you think about keeping your business moving. Featuring an innovative two-stage turbocharged, low-emissions diesel engine and dual-clutch automatic transmission, you'll benefit from increased fuel savings, enhanced efficiencies, higher payload capacity, and improved driver productivity. Add to this our 5-year/175,000-mile powertrain limited warranty and you get the longevity and durability you can expect from FUSO.



WEIGHT RATINGS	GVWR/GCWR	13,200 lb./20,915 lb.			
	GAWR (front/rear)	5,360 lb./9,880 lb.			
CURB WEIGHT	Base model	5,225 lb. (est.)			
BODY/PAYLOAD	Estimated max.	7,975 lb. (see dealer for details)			
DIMENSIONS	Wheelbase	110.2" (C)	133.9" (E)	151.6" (G)	169.3" (H)
	Overall length (cab/chassis)	204.9"	228.5"	246.3"	264.0"
	Usable cab to rear axle	81.2"	104.9"	122.6"	140.3"
	Body sizes accommodated	10' to 20'			
ENGINE	Model	FUSO 4P10-T5 Diesel			
	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder, with high-efficiency electrically-engaged cooling fan			
	Displacement/Emissions	183 cu. in. (3.0 L) Electronically controlled DPF/SCR system with OBD			
	Max. output (SAE, gross)	161 hp @ 3,400 rpm			
	Max. torque (SAE, gross)	295 lb.-ft. @ 1,300 rpm			
AIR CLEANER	Type	Dry paper element with snorkel			
TRANSMISSION	Standard equipment	M038S6 DUONIC® 6-speed dual-clutch automatic			
AXLE CAPACITY	Front/Rear	5,735 lb./9,925 lb.			
FINAL REDUCTION GEAR	Type	Single-reduction hypoid			
	Ratio (std./opt.)	4.875/5.285			
TOP SPEED, EST.	Std. diff./Opt. diff.	90/83 mph			
TURNING DIAMETER	Minimum, by wheelbase	34.1'	40.0'	44.6'	49.5'
TIRES (PREMIUM)	Configuration	Single front, dual rear			
	Size/Type	215/85R16 10PR LR:E/All-season all positions			
WHEELS	Size/Configuration	16" x 6"/5-lug			
STEERING	Type	Ball-nut type with integral-type hydraulic power boost			
	Adjustments	Tilt/telescoping steering column with steering lock			
SUSPENSION	Front	Laminated leaf springs with shock absorbers and stabilizer bar			
	Rear	Laminated leaf springs with shock absorbers			
BRAKES	Service	Dual-caliper discs, vacuum/hydraulic-type with ABS			
	Parking	Drum/driveline, internal expanding shoe			
	Exhaust	Electrically actuated			
FRAME	Type	Ladder/straight			
	Section modulus	7.08 cu. in. per rail			
	Yield strength	56,565 psi			
	RBM per rail	400,410 lb.-in.			
	Height/Width	32.5"/33.5"			
	Environmental durability	Premium anti-corrosion package for frame and frame-mounted components			
FUEL TANK	Capacity/Location—std.*	30 gal./in-frame, aft of rear axle			
	Capacity/Location—opt.**	33 gal./left side			
DEF TANK	Capacity/Location	3.2 gal./right side			
BATTERY	Type/Capacity	Two 12-volt, maintenance-free/750 CCA			
ELECTRICAL	Starter/Alternator	12-volt/12-volt, 140A output			
COLD WEATHER	Starting/Operation	Ceramic glow plugs/PCV heater, DEF tank heater			
CONVENIENCE/ASSURANCE	Windows/Door locks	Power-operated, one-touch up and down driver's side window			
	Cruise control	Standard (programmable)			
	Entry	Keyless, with driver/assistant door lock control			
	Radio	Clarion AM/FM/CD, hands-free Bluetooth® (optional)			
	Air conditioning	Standard factory-installed			
	Idle Limit System (ILS)—opt.	Automatic engine shutdown of stationary vehicle, in Park or Neutral, after achieving normal operating temperature with dealer-programmed limit of 3, 5, or 10 minutes			
	Collision avoidance system	Mobileye® 6 Series (optional)			

KEY BENEFITS

- On the lighter end of our medium-duty lineup, this is a great choice for appliance and package delivery, office supplies, or air cargo
- Our exclusive DUONIC® dual-clutch automatic transmission offers effortless navigation of city streets and heavy traffic
- Enjoy the long haul in our most comfortable cab ever, fully equipped with an ergonomically designed interior, adjustable steering wheel, and spacious seating and stowage
- From sunrise to sundown, a panoramic windshield and a driver-to-ground line of sight of only 6 ft. ensure you stay focused on what's ahead
- Go further on less with our ultra-efficient advanced dual-turbo diesel engine with access to high torque whenever it's needed
- Mobileye®¹ system provides audible and visual alerts for speeding, lane departure, potential pedestrian or vehicle collisions

¹Optional feature

CAB COLORS

ARCADIA SILVER	MARS RED
NATURAL WHITE	SHANNON BLUE
JUPITER GREEN	SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

FABRIC STYLE



Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. Please see your local dealer for details and warranty limitations.

*rear fuel tank is not designed for use as a primary or auxiliary in any dual tank system

**133.9", 151.6", 169.3" wb

PRINTED IN THE U.S.A.

©2017 MITSUBISHI FUSO TRUCK OF AMERICA, INC.

MITSUBISHI FUSO TRUCK OF AMERICA, INC.

2015 Center Square Road
Logan Township, NJ 08085

MITFUSO.COM

