


NON-90 DEGREE TRANSITION COPING MITER




OUTSIDE MITER

- TAPERED COPING
- FLAT COPING





ANSI/SPRI ES-1*



INSIDE MITER

- TAPERED COPING
- FLAT COPING



MATERIAL (please choose one):

- | | |
|----------------------------------------|----------------------------------------|
| <input type="checkbox"/> 24 GA Steel | <input type="checkbox"/> .040 Aluminum |
| <input type="checkbox"/> 22 GA Steel | <input type="checkbox"/> .050 Aluminum |
| <input type="checkbox"/> .032 Aluminum | <input type="checkbox"/> .063 Aluminum |

Other: _____
 Color: _____
 Finish: _____

Quantities:

_____ Outside Miter(s)
 _____ Inside Miter(s)
 _____ Degree Angle

Miter/End Cap Fabrication Requirements:

- | | |
|---------------------------------------------|---------------------------------------------|
| <input type="checkbox"/> Pop Rivet & Sealed | <input type="checkbox"/> Welded (see note)* |
|---------------------------------------------|---------------------------------------------|

Installation:

- 1) Cleats are to be installed 40" O/C, coping hem crimped to cleat
- 2) 8 - 1.5" SS Ring Shank nails per cleat, minimum
- 3) Splice plates require 2 beads of sealant per side of coping

Sheet ___ of ___

DWG# 740-013

Notes:

- 1) *Accessory Welding is only available in 040 aluminum or heavier
- 2) External splice plates are available upon request
- 3) Written approval is required prior to fabrication, contractor is responsible for all dimensions and quantities. Fabricated items are not returnable.

Temple Architectural Products
 638 Moore Rd
 Avon Lake, OH 44012

Phone: (216) 440-3595
 Alternate: (330) 348-3983
 Fax: (440) 653-9883

Project Name: _____

Installing Contractor: _____

Contact Name: _____

Contact number: _____

Signed Approval: _____