



2002 Suzuki Suspension Specs

| [1997](#) | [1998](#) | [1999](#) | [2000](#) | [2001](#) | **2002** | [2003](#) | [2004](#) | [2005](#) | [2006](#) | [2007](#) | [2008](#) | [2009](#) | [2010](#) | [2011](#) | [2012](#) | [2013](#) | [2014](#) | [2015](#) |

Model	Fork Size	Manufacturer	Fork Rate	Oil Level	Rear Spring	Race Sag	Weight	Suggestions
RM 85	37mm	Showa	0.26	110mm	4.9kg	90mm	120lbs ±10	Forks soft
RM 125	47mm	Showa Twin Chamber	0.40	130mm	4.8kg	90mm	155lbs ±10	Well balanced bike, forks may be soft for 160 lb expert.
RM 250	46mm	KYB	0.43	100mm	4.8kg	90mm	170lbs ±10	Tech-Care recommends 2 stage forks, 3 stage rear shock. Rear is over sprung
DRZ 400	49mm	Showa	0.43	125mm	5.2kg	95mm	160lbs ±10	Go to stiffer fork and shock spring if over 175lbs

2002 Suzuki Suspension Tips

Model	Tips
RM 250	Very easy to ride. Motor has more top end power, it has more over rev compared to last year. Suspension is better than last year. forks and shock will soak up braking bumps and resist bottoming. For a more aggressive racer and heavier, the suspension may be found under sprung and a little light on the compression valving on the forks. tech-Care has a great modification for your weight and ability.
RM 85	This bike has been improved greatly from past years. With new Showa inverted forks, new cylinder, carb and other improvements. Forks are a little soft compared to rear shock. We suggest a 4.7 spring or go up to a .28 fork spring. Call for valving modifications.



Copyright 2016, Tech-Care Suspension **Store Hours: Mon. - Fri: 9a.m. - 6p.m. Sat: 9a.m. - 4p.m.**