



STM v1.4 mini

Smart and Customizable “mini” Tinting Machine

- Product design and the technical features may change without notice.

Yiğın Global Trade Inc.

Kanuni Mah. 772. Sok. 33/A, Keçiören, Ankara, 06280 TURKEY



+905322475192



alper@yigin.com

www.yigin.com



STM v1.3



Easily adjustable elevator for degraded tinting.
Customizable size and position for the desired degrading level.

* All tanks are capable of degraded tinting.

User friendly HMI Screen for simple and easy process control.
Each tank can be programmed individually.
Programmable degrade tinting function is under development.



Durable electropolished stainless steel tanks.
Computer controlled, accurate temperature stabilization with sensors for stable color results. Two step heating function helps you to save energy.

60cm long rinsing tank for convenient cleaning.



Integrated automatic fill* and drain system with a 3-way valve ensures economy and a fast process.
3-way valve allows you to flush either in a tank or drain to the sewage, depending on your local regulation.

* The one and only system on the market.

Technical Details

106 x 74 x 190 cm / 42 x 29 x 75 inches | ~350 kg. / 770 lbs | 10KW / 400 V 3PH | Compressed Air (4 - 6 bar) needed for pneumatic functions

Tank number: 10 | Lenses per tank: 4 | Lens Size: 40 mm - 85 mm | Lens holder quantity: 5

For all tintable indexes

CE, ISO 12100:2010, EN60204-1 certified production

Options:

- Lens Holder (5 holder set included)
- Color control unit on the side. (adjustable from 3000K to 6500K)

• Product design and the technical features may change without notice.



Advanced stirring by a propeller in each section ensures homogenous dye mixture and temperature.

Yiğın Global Trade Inc.

Kanuni Mah. 772. Sok. 33/A, Keçiören, Ankara, 06280 TURKEY

+905322475192

@ alper@yigin.com

www.yigin.com

YGIN
GLOBAL TRADE INC.