



Stainless Steel Screen Filter Cartridges

EC-90 Series

Features & Benefits

Manufactured of AISI304 stainless steel with silicone gaskets. Fit standard sized 2.5"OD & Big-Blue 4.25"OD cartridge housings. These high-durability screen mesh filters are cleanable. Can be back-washed, soaked, hosed-down, or scrubbed to remove accumulated particulate and provide many years of dependable service. Suitable for use with potable water and food products.

Applications

- Whole-house filtration of sand & sediment
- Protection of softeners, water heaters, pumps, & valves
- Extending life of downstream final filters
- Irrigation water
- Fluids with high solids load
- Machining fluids
- Industrial fluid treatment



Model	OD	Length	Rated Flow	Rating
EC-90-10 \underline{X}	2.50"	10"	10 gpm	\underline{X} =
EC-90-20 \underline{X}	2.50"	20"	20 gpm	10 = 10 μ
EC-90J-10 \underline{X}	4.3"	10"	18 gpm	25 = 25 μ
EC-90J-20 \underline{X}	4.3"	20"	36 gpm	50 = 50 μ
				100 = 100 μ

Max. Operating Temperature: 300°F (150°C)

Recommended Differential Pressure for Cleaning: 60 psid (4 bard) max.

EMD Global

Loveland, CO USA
+1.970.443.9376

www.emdglobal.net
info@emdglobal.net