



**SUBMITTAL DATA
SHEET METAL FITTINGS**

**Flange & Gasket
HETO**

HETO Fittings

(Tolerance on all sizes +/- 1/8")

Nom. Dia.	Sleeve O.D.	Opening Dimensions	Length No Damper	Length With Damper	Flange O.D.
5"	4.875	5 x 9	12	12	7 x 11
6"	5.875	5 x 9	12	12	7 x 11
8"	7.875	6 x 12	12	12	8 x 14
10"	9.875	8 x 14	12	12	10 x 16
12"	11.875	10 x 16	12	12	12 x 18
14"	13.875	12 x 18	12	12	14 x 20
16"	15.875	14 x 20	12	12	16 x 22
18"	17.875	16 x 22	12	12	18 x 24
20"	19.875	18 x 24	12	12	20 x 26

Flange – 1" wide, galvanized steel, closed corners

Gasket - 1/8" PE Foam, PSA

Fitting Model

- HETO No Damper
- HETOD Standard Damper – Spring End Bearing with Handle and Wingnut
- HETOD1 2" Damper Handle Extension
- HETOD3 2" Buildout – 3/8" square shaft, Nylon End Bearings and Locking Handle

Standard Construction

- Galvanized Steel, 26 Ga. thru 12" Dia., 24 Ga. on 14" Dia. and above

Gauge Options

- 24 Gauge
- 22 Gauge
- 20 Gauge
- Other _____

Material Options

- Galvanized Steel
- Aluminum
- Stainless Steel
- Other _____