



## LED 10" COMMERCIAL DOWNLIGHT

LED 10" LED COMMERCIAL DOWNLIGHT SERIES has been designed and engineered for commercial application, retrofitting existing recessed 10" can housing as well as new construction application. It has a CRI > 80 with high system efficiency. It is suitable for offices, retails, hospitals, hotels, schools, warehouses and factories.

### FEATURES


- Superior quality white LED light
- Driver efficiency > 85%
- Aluminum heat sink
- Comfortable diffused light
- High thermal conductivity
- Efficacy > 75 Lm/W
- Dimmable
- High Power Factor > 0.9
- Standard lifetime 50,000 hours
- High CRI > 80
- Working temperature: -4°F~+122°F
- Input Voltage 100-277VAC



### OPTIONS

- TRIM - white or other color
- Reflector - Specular or Matte diffuse
- Diffuser - Frosted or Opal

**5 Years Warranty**



Manufactured by:



| Model              | Watts | CTT                        | Lumens | CRI | Size               | PF   | Cover        |
|--------------------|-------|----------------------------|--------|-----|--------------------|------|--------------|
| GAI-04-RD-10-34W-X | 34    | 2700K, 3000K, 3500K, 4000K | 2500   | >80 | (A)8.89"x(B)10.98" |      |              |
| GAI-04-RD-10-40W-X | 40    | 2700K, 3000K, 3500K, 4000K | 3000   | >80 | (A)9.21"x(B)10.98" | >0.9 | Frosted Opal |
| GAI-04-RD-10-42W-X | 42    | 2700K, 3000K, 3500K, 4000K | 3500   | >80 | (A)9.21"x(B)10.98" |      |              |
| GAI-04-RD-10-50W-X | 50    | 2700K, 3000K, 3500K, 4000K | 4000   | >80 | (A)9.21"x(B)10.98" |      |              |