

11.000" OD X 3.000" ID DRILL COLLAR, SLICK, AISI 4145, 7-5/8" REG (LOW TORQUE FACE)

DRILL COLLAR BODY

Nominal OD (in)	11.000
Nominal ID (in)	3.000
Pipe Wall Thickness (in)	4.000
Surface Finish	SLICK
Grade	AISI 4145
Cross Sectional Area of Pipe Body (in ²)	87.965
Cross Sectional Area OD (in ²)	95.033
Cross Sectional Area ID (in ²)	7.069
Section Modulus (in ³)	129.948
Polar Section Modulus (in ³)	259.896
Momet of Inertia Drill Collar Body (in ⁴)	714.71
Polar Moment of Inertia Drill Collar Body (in ⁴)	1,429.42

DRILL COLLAR CONNECTION

Connection	7-5/8" REG (LOW TORQUE FACE)
OD (in)	10.000
ID (in)	3.000

DRILL COLLAR ASSEMBLY

Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	4.57
Closed End Displacement (gal/ft)	4.94
Fluid Capacity (gal/ft)	0.37
Drift Size (in)	2.875

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.