

Wireless 720P Pan& Tilt IP Camera



1. Product Feature

- ✧ 1/4" line scanning digital and advanced DSP technology
- ✧ Picture Resolution 720P color CMOS , 1.0 Mega Pixel, 1280X720
- ✧ Optimized H.264 Main Profile compression algorithm, high compression ratio and high quality image; convenient to realize a transmission of HD images on a narrow band, thus it can save the storage space; support triple bit streams
- ✧ The most advanced network delivery server technology ,Easily achieve more user access , Multi-stage user password rights management
- ✧ Built in Web Server, through the IE browser easy to realize the remote control Settings prison see operation
- ✧ Support facilities remote security upgrade function
- ✧ Support DDNS ,PPPoE and (UPnP) ,Support Lan ,Wan transport.
- ✧ Technology of self adaptability to network that it may adjust its video flame rate automatically according to the bandwidth of network
- ✧ Functions of alarm in video missing, mobile detection or probe, etc. (available to set the regions and sensitivity)
- ✧ Support mobile detection / image shielding / image snapshot
- ✧ Functions of auto recovery in abnormality and auto reconnection in network breakdown



2. Product Specification

Model		IP3F32P-IR-W
Camera	Pixel	1.0 Mega Pixel, 1280*720
	Lens	3.6mm(2.8mm/6mm lens optional)
	Electronic shutter	1/25s-1/30,000s
	Low Lux	Color: 0.1Lux@F1.2 B/W: 0Lux@F1.2
	ICR	Support
	Video parameter	Saturation, brightness, contrast ratio and color tone can be adjusted by customer end or IE explorer
IR	IR Properties	Dual filter day / night: automatic switch, linkage switch
	IR Light	IR Distance: 10M
Audio-video coding parameters	Compression	H.264 Main Profile @Level 3.0 / MJPEG optional
	Video bit rate	0.1M-6Mbps, customized
	Bit stream type	video stream
	Audio compress	G.711 Optional
	Audio bit rate	8~16kbps
	Triple bit streams	Support
Image	Video resolution	1280*720
	Video flame rate	PAL: 1-25 frames/second, NTSC: 1-30 frames/second
Function	PTZ	Pan: 355°, Tilt: 90°
	Heartbeat mechanism	Support
	IP auto pop-out	IP auto pop-out at customer end
	Password protection	Multi-level protection on password
	Intellectual alarm	Mobile detection, video shielding, video loss, network breakdown, abnormality in storage
	Basic functions	One-key reset, password protection, watermark technology
Interface	Audio input	Built-in Microphone
	Audio output	Built-in speaker
	Alarm input	1ch in
	Alarm output	1ch out
	Network port	1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port
	Mini SD Card slot	1pcs, support up to 64GB
Wireless network	WIFI	Support(support setup IP address via mobile app or PC)
	Wireless encryption protocol	WPA, WPA2, WEP, WPS
	Mobile Phone monitor	Camviews(support Zoom in/out, QR-Code scan, Record/playback)
others	Power supply	DC5V/1.5A
	Power consumption	<6W
	Working temp	-10℃ ~ +55℃
	Working humidity	10 ~ 85%