

2-7/8" OD TUBING, 6.50 PPF, L-80, EUE (8RD)

## TUBING BODY

|                         |       |
|-------------------------|-------|
| Nominal OD (in)         | 2-7/8 |
| Nominal ID (in)         | 2.441 |
| Nominal Weight (lbs/ft) | 6.50  |
| Grade                   | L-80  |

## TUBING CONNECTION

|                                 |           |
|---------------------------------|-----------|
| Connection                      | EUE (8RD) |
| Connection OD (in)              | 3.668     |
| Connection ID (in)              | 2.441     |
| Minimum Make-up Torque (lbs/ft) | 1,690     |
| Maximum Make-up Torque (lbs/ft) | 2,810     |

## TUBING ASSEMBLY

|                                  |       |
|----------------------------------|-------|
| Open End Displacement (gal/ft)   | 0.09  |
| Closed End Displacement (gal/ft) | 0.34  |
| Fluid Capacity (gal/ft)          | 0.24  |
| Drift Size (in)                  | 2.347 |

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.