

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Porcelanato

TECHNICAL CHARACTERISTICS

Available Formats:	36x36 BIANCO CARRARA POLISHED		
Style Description:	Polished Glazed Porcelain	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Polished	Number of Faces/Screens:	6
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Glossy/Polished
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	<0.4
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	3	Breaking Strength:	>1500
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GLB		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.65	Pieces per Carton:	2
SqFt per Pallet:	882.50	Pounds per Carton:	
Boxes per Pallet:	50	SqFt per Container:	
Pallets per Container:	15		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Porcelanato

TECHNICAL CHARACTERISTICS

Available Formats:	36x36 BIANCO CARRARA MATTE		
Style Description:	Glazed Porcelain	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Matte	Number of Faces/Screens:	6
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	<0.4
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	3	Breaking Strength:	>1500
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GLB		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.19	Pieces per Carton:	2
SqFt per Pallet:	909.50	Pounds per Carton:	
Boxes per Pallet:	50	SqFt per Container:	
Pallets per Container:	15		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Porcelanato

TECHNICAL CHARACTERISTICS

Available Formats:	36x36 ANTIQUE OFF WHITE POLISHED		
Style Description:	Polished Glazed Porcelain	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Polished	Number of Faces/Screens:	8
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Glossy/Polished
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	<0.4
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	3	Breaking Strength:	>1500
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GLB		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.65	Pieces per Carton:	2
SqFt per Pallet:	882.50	Pounds per Carton:	
Boxes per Pallet:	50	SqFt per Container:	
Pallets per Container:	15		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".