AUTOCLAVE (HORIZONTAL) RIC-34CH



Inner chamber made of Stainless Steel (304 Grade), Outer Body Made of thick Mild Steel finished with Hammer Tone Paint/ S.S. Coated, Head made of Mild Steel- S.Steel lined. Pressure gauge. Provided with Radial locking system, safety device and with S.S. basket, water level indicator. Pressure up to 20 PSI, Complete with plug in Cord to work on 220 volts. A.C. Optional PID Control temp. controller.

Model No.	Height X Dia	Load	Capacity (Lit.)
RIC-34CH-A	450mm x 250mm (18" x 10")	1.5 KW	22
RIC-34CH-B	500mm x 300mm (20" x 12")	2.0 KW	36
RIC-34CH-C	550mm x 350mm (22" x 14")	3.0 KW	50
RIC-34CH-D	600mm x 450mm (24" x 18")	6.0 KW	98
RIC-34CH-E	750mm x 550mm (30" x 22")	7.5 KW	152
RIC-34CH-F	1100mm x 400mm (44" x 16")	9.0 KW	200

FEATURES:

- Chamber, Constructed from S.S 304 Grade
- Lid Closing by Radial Locking System
- Sealing of lid by Neoprene Rubber Gasket
- Chamber Insulated by Mineral/Glass Wool
- Over Pressure Safety by safety Valve.
- Continuous Monitoring of Pressure
- Water level Indicator
- Sterilizing Temperature upto 134°C
- Sterilizing Pressure up to 2.1kg/cm2
- Tested up to 2.5 times of required pressure
- Voltage: 220Volts AC (50HZ)



RELIABLE INSTRUMENTS CO. (ISO 9001CO.)

Sales/Reg. Office: 301, 2nd Floor, Mittal Commercial Complex, N.I.T-5, Faridabad Tel.: 91-129-4052611, 2410244, 6450611; Telefax: 91-129-2410219; M: 91-9818047375

Email: ricindfbd@gmail.com; ricind@rediffmail.com; ricind@yahoo.co.in;

Web: www.ricind.com

Web: www.ricind.net/ www.ricind.com