

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Morella

## TECHNICAL CHARACTERISTICS

Available Formats:	18x18, 13x13, 3x3 Mosaic 12x12 Sheet, 3x13 Bullnose		
Style Description:	Marmo	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Travertine	Number of Faces/Screens:	10
Thickness in mm:	8mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	Red body
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<0.40
Scratch Hardness (MOHS)		Breaking Strength:	800N
Frost Resistant:	No	Thermal Shock Resistance:	No
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	GB		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	24.76	Pieces per Carton:	10
SqFt per Pallet:	1386.56	Pounds per Carton:	71.56
Boxes per Pallet:	56	SqFt per Container:	20798.40
Pallets per Container:	15		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".