



C100E



C100E

C100REFURBISHED2015

CLAM 48"X35"H,1 PH,240V-LAF STEEL CONST W/POLYURETHANE EXT. 5HP, 50PSI, 120GPM PUMP. CAP 225 GAL , 3000 LB TURNTABLE CAP. 240 V, 1 PH NEMA 4, 24/7 HEATER TIMER. SUMP INSULT. 1ST & 2ND STAGE 304S FILTERS-

New pump assembly, New heaters, New paint, All parts will replaced as needed

Machine will carry a Standard CLAM warranty.

[Call For Price](#)

FEATURES	C100E
External Dimensions	
Width	71"
Depth	74"
Height Closed	68"
Height Opened	111"
Turn Table Diameter	52"
Working Height	42"
Capacity in Lbs. Loading	3000 Top
Solution Reservoir Gals.	150
Cabinet Construction Insulated	Dual Steel Lower
Lid Operation	Semi-Auto
Cycle Timer Spring/Min. 0-120	Included
Electrical Power	NEMA4
Single Phase (Standard)	208/240V
Three Phase	208/480V 2
Amps (Standard Phase)	70
Heating Element	12KW
Pump	Cast Iron
Horse Power	5
PSI	50
Gpm	120
Particle Filter	
First Stage	Included
Pump Filter	Included
Oil Skimmer	Included
Low Water Shut Off/ Auto Water Fill	Option
Timer-24 Hour/7 Day	Included
Rinse Cycle (Stainless Steel) To Tank	Option
Rinse Cycle (Stainless Steel) to Drain	Option
Rinse Supply Tank (304 Stainless Steel)	Option
Low Micron (5-100 Micron) Bag Filter	Option
Spray Wand	Option
3-Phase Power 50/60 Cycle 380/600 Volt	Option
Production Start/ Stop Light	Option
Compressed Air Blow Dry	Option
Hot Air Blow Dry	Option
CLAM® Clean Out Pump	Option
Warranty	1-Year