

PRO STREET SEMI

- 1) *Maximum 20,000# with the hitch. Weights cannot extend past the hook point.*
- 2) *Maximum hitch height is 20". Hitch will be measured in the pull position with suspension inflated and limiting devices tight. Hitch must pull from factory 5th wheel. Center of 5th wheel must be located in a position between the center of the front drive axle and the center point between the drive axles. There must be a minimum of 66" of unobstructed area from the center of 5th wheel forward to the first obstruction (cab, sleeper, toolbox, headache rack etc.) Hook point cannot exceed 7 feet from the center of the rear axle.*
- 3) *Turbo: 4.1" inlet with maximum MWE groove of .250". MWE groove must be 90 degrees to the face of the wheel. Only exclusion is for non-altered factory twins in stock location.*
- 4) *SFI scatter blanket or 3/8" plate, Min. 16" wide surrounding flywheel housing required.*
- 5) *SFI certified flywheel required.*
- 6) *Harmonic balancer shielding required. Minimum shielding is a cross bar no farther forward than 1" in front of balancer to prevent balancer from walking forward. If crossbar is not mounted directly to block it must have 2 tabs facing rearward, extending as close to front of motor as possible. Tabs should be 180 degrees from each other and within 1" of balancer. Min. 1/4" thick steel and 2" wide. If front engine mount and crossmember do not extend below balancer, a 1/4" thick steel plate will need to be mounted below balancer. Plate must be large enough that in the event of breakage it would not allow balancer to fall on the ground.*
- 7) *Must have (2) 1/2" exhaust cross bolts within 1" of each other and as close to charger as possible.*
- 8) *Side shields required. Must extend from top of frame to the block/head mating line and cover the entire length of the block. Min. 1/8" steel or 3/16" aluminum.*
- 9) *2 engine safety cables required. Front cable must be 1/2" diameter and located between cylinders 1&2. Second cable must be minimum 3/8" diameter and located between cylinders 2&3. Both cables must have 2 clamps per cable.*
- 10) *Any U-Joint visible from side of truck must be shielded. Shielding must be full 360 degree enclosure, minimum 6" long and 1/4" steel or 5/16" aluminum.*
- 11) *Driver must wear a DOT or Snell approved helmet.*
- 12) *Water injection is not allowed.*
- 13) *Vehicle must have an air shutoff connected to hitch. A 2" steel ring secured with a 15# zip tie within 6" of hook point required.*