

BarnLiter™ /NiteLiter™ Series**Features and Specifications****Applications**

Demanding interior environments that require an enclosed fixture. Ideal for dairy herd management.

Certification

UL Listed for Wet Locations. IP65 Certified.

Construction

Sealed and gasketed aluminum body and lens frame. Stainless steel exterior hardware. Rubber silicone washers used to seal fasteners.

Electrical

Hardwired, water tight connection with pre-wired whip. Instant and program start ballasts available.

Reflectors

Patented, optically efficient reflector design provides 95% total reflectance.

Finish

Bronze powder coated exterior aluminum surface and lens frame carry a 10 year appearance warranty.

Warranty

Orion fixtures are covered by a one-year limited warranty. Accessories and individual components are covered by separate OEM supplier warranties.

**WTAGB****Required Ordering Information**

1 Select	WTAGB
Series	
WTAGB	Wet Tested Enclosed BarnLiter Fixture with Quick-Disconnect Brackets

2 Select	Number of Lamps	
4	4-Lamp T8	
6	6-Lamp T8	
8	8-Lamp T8	

3 Select	Ballast Type	
(blank)	Instant Start	
PS	Program Start	

4 Select	Switching	
DS3	Dual Switching, NiteLiter System (1 lamp on at night, 5 off)	
DS	Dual Switching	

5 Select	Additional Options	
(blank)	No Internal Transformer	
TF	Internal Transformer, 480v	

6 Select	Lamp Type	
(blank)	850 Lamps*	
841	841 Lamps*	

*Add "HL" to Lamp Type suffix for High Lumen
Add "SR" to Lamp Type suffix for Shatter Resistant.
Add "HLSR" to Lamp Type suffix for High Lumen Shatter Resistant.

7 Select	Connection Options	
6W	6' Whip	
11W	11' Whip	
CE7	7' Hardwire Leads with water tight Elbow Connector	

8 Select	Reflector Options	
(blank)	Low Bay Reflector	
CMR	High Bay Reflector	

Options (must be ordered separately)

-Quick Disconnect Flush Mount Brackets (Short and Tall options available)

Orion Energy Systems

Physical and Performance Information¹

Part Number	Number of Lamps	Wattage Consumed		Line Amps	Length	Width	Depth	Weight ²
		120 thru 277v	480v					
BarnLiter™ WTAGB4HL6W	4 Lamp T8	147	155	1.23@120v 0.61@240v 0.32@480v	48.5"	13.69"	5.63"	16.0 lbs.
NiteLite™ (Full NiteLite Mode) WTAGB4DS3HL6W	4 Lamp T8	135	142	1.13@120v 0.56@240v 0.30@480v	48.5"	13.69"	5.63"	17.0 lbs.
NiteLiter™ (NiteLite Mode) WTAGB4DS3HL6W	4 Lamp T8	25	26	0.21@120v 0.10@240v 0.05@480v	48.5"	13.69"	5.63"	17.0 lbs.
BarnLiter™ WTAGB6HL6W	6 Lamp T8	221	232	1.84@120v 0.92@240v 0.48@480v	48.5"	18.94"	5.63"	21.0 lbs.
NiteLiter™ (Full NiteLite Mode) WTAGB6DS3HL6W	6 Lamp T8	209	219	1.74@120v 0.87@240v 0.46@480v	48.5"	18.94"	5.63"	22.0 lbs.
NiteLiter™ (NiteLite Mode) WTAGB6DS3HL6W	6 Lamp T8	25	26	0.21@120v 0.10@240v 0.05@480v	48.5"	18.94"	5.63"	22.0 lbs.
BarnLiter™ WTAGB8HL6W	8 Lamp T8	294	309	2.45@120v 1.23@240v 0.64@480v	48.5"	24.19"	5.63"	27.0 lbs.
NiteLiter™ (Full NiteLite Mode) WTAGB8DS3HL6W	8 Lamp T8	283	296	2.36@120v 1.18@240v 0.62@480v	48.5"	24.19"	5.63"	28.0 lbs.
NiteLiter™ (NiteLite Mode) WTAGB8DS3HL6W	8 Lamp T8	25	26	0.21@120v 0.11@240v 0.05@480v	48.5"	24.19"	5.63"	28.0 lbs.

Additional Specification Information:

¹Actual performance may vary by up to ±10% of values listed.

²120–277 voltage standard. Also available for 347v or 480v systems with addition of optional transformer; increases overall weight by two pounds and wattage consumption by approximately 5%.



855-836-2577

www.oesx.com

NYSE MKT: OESX

©2013 Orion Energy Systems, Inc. All rights reserved. Light Years Ahead and Orion are trademarks/service marks of Orion Energy Systems Inc. Design modification rights reserved.

2 0131203



Made in USA