

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

ANTHOLOGY

## TECHNICAL CHARACTERISTICS

Available Formats:	18x36, 12x24, 15x14 Hexagon, 15x14 Hexagon Mosaic Sheet, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Mixed Marble/Stone	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	18x36: 9; 12x24: 24
Thickness in mm:	10	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	32%	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet: 0.70 Dry: 0.60
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	6	Breaking Strength:	≥ 35N/mm
Frost Resistant:	Yes	Thermal Shock Resistance:	ISO 10545-7 Resistant
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	ASTM C-650		

## PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	12.06 / 16.04 (A)	Pieces per Carton:	6 / 8 (A)
SqFt per Pallet:	482.40 / 481.20 (A)	Pounds per SqFt:	4.05 / 4.05 (A)
Boxes per Pallet:	40.00 / 32.00 (A)	SqFt per Container:	12060.00 / 14436.00 (A)
Pallets per Container:	25.00 / 30.00 (A)		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".