

TRUE[®] CARDIO

CS650 COMMERCIAL



PREMIUM FITNESS EQUIPMENT SINCE 1981

CS650 TREADMILL

At TRUE, we understand that you need quality, dependable equipment to grow your business and make your customers happy with the results they achieve. We build our cardio equipment with you in mind. With over 35 years of experience, we know what it means to deliver quality cardio equipment. Our entire process, from design to testing, ensures that TRUE is the most premium cardio equipment on the market today. Let TRUE be your cardio partner to furnish your facility with premium machines that will exceed your users' expectations.



CS650
TECHNICAL SPECIFICATIONS

Power Source	110V/20A, 220V Option Available
Cord Length	12' / 3.7M
Drive Motor	5 HP AC Self-Cooling Max Drive
Incline Motor	1,200 lbs. of thrust
Speed Sensor	Optical
Deck	Reversible 1" / 0.8 cm Medium Density Fiberboard
Reversible Deck	Standard
Belt	Siegling Multi-Ply with PVC Coating
Rollers	3" / 8 cm w/ Sealed Bearings
Impact System	True Soft System
Frame Construction	Robotically Welded Heavy-Gauge Steel
Lubrication	Silax
Speed Range	0.5 to 12.0 MPH / 0.8 to 19.3 KMH
Incline/Decline Range	0% to 15%, (Optional -3% to 15%)
Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point
Handrail Design	Extended Handrails with Molded Rubber, Moisture Resistant Grips
Contact Heart Rate Monitoring	Yes
Wireless Heart Rate Monitoring	Polar®

AVAILABLE CONSOLES Transcend¹⁶, Transcend¹⁰, Escalate¹⁵, Escalate⁹, Emerge

SAFETY	Safety Clip Standard
	Extended Handrails Standard
	Large Straddle Covers Standard

User Detection User Present Detection™

REGULATORY APPROVALS ETL UL1647, CSA, CE, EN957, FCC

EXTRAS **Accessories** Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder

PHYSICAL SPECIFICATIONS	Footprint 82" L x 33.8" W / 208 cm x 86 cm
	Running Surface 60" L x 22" W / 152 cm x 56 cm
	Machine Weight 420 lbs / 91 kg
	Shipping Weight 462 lbs / 210 kg
	Maximum User Weight 500 lbs / 226 kg
	Step-Up Height 7" / 17 cm 9" / 23 cm With optional decline
	Portability 2 Front Transport Wheels

WARRANTY	Warranty Type Commercial (all dues paying facilities, regardless of usage)
	Frame Lifetime
	Motor 5 Years
	Parts 3 Years
	Labor 3 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

