

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

COMO

TECHNICAL CHARACTERISTICS

Available Formats:	20x20, 3x20 Bullnose	Glaze Application Method:	Rotocolor
Style Description:	Chiseled-edge	Number of Faces/Screens:	N/A
Visual Characteristics:	Rustic Stone	Number of Punches/Molds:	1
Thickness in mm:	N/A	Body Type:	Porcelain (<.5%)
Modular Suitability:	Yes	Color Body Unglazed:	No
Application:	Residential/Commercial	Surface Type:	Matte
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	No Less than 3/16"
Rectified:	No		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	Wet: 0.55 Dry: 0.89
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.51
Scratch Hardness (MOHS)	7	Breaking Strength:	1715
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	N/A		

PACKING INFORMATION

SqFt per Carton:	16.14	Pieces per Carton:	6
SqFt per Pallet:	581.04	Pounds per Carton:	63.92 lbs
Boxes per Pallet:	36	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".