




2018 SYC OPEN



DISTANCE:	42 FEET	VOLUME:	25.285 mL
RATIO:	7.26:1	FORWARD:	17.185 mL
DROP BRUSH:	33 FEET	REVERSE:	8.1 mL
TANKS:	KEGEL & KEGEL	PUMP:	MULTI



FORWARD LOADS DATA


#	START	STOP	LOADS	MICS	SPEED	BUFF	TANK	DISTANCE	T.OIL
1	2L	2R	3	45	14	4	A - Kegel	0 → 4	4,995
2	8L	8R	2	45	18	4	B - Kegel	4 → 9	2,250
3	9L	9R	3	50	18	3	A - Kegel	9 → 17	3,450
4	10L	10R	3	55	18	3	B - Kegel	17 → 24	3,465
5	11L	11R	2	55	18	3	A - Kegel	24 → 29	2,090
6	12L	12R	1	55	22	3	B - Kegel	29 → 32	935
7	2L	2R	0	50	22	3	A - Kegel	32 → 35	0
8	2L	2R	0	50	26	2	B - Kegel	35 → 42	0

REVERSE LOADS DATA

#	START	STOP	LOADS	MICS	SPEED	BUFF	TANK	DISTANCE	T.OIL
1	2L	2R	0	40	30	3	B - Kegel	33 → 32	0
2	13L	13R	3	50	22	3	A - Kegel	32 → 23	2,250
3	11L	11R	2	55	22	3	B - Kegel	23 → 17	2,090
4	10L	10R	2	55	18	3	A - Kegel	17 → 12	2,310
5	6L	6R	1	50	18	4	B - Kegel	12 → 9	1,450
6	2L	2R	0	50	14	4	A - Kegel	9 → 0	0

THIS PATTERN IS DESIGNED FOR:

VARIABLE BUFFER SPEEDS | VARIABLE MICROLITER STREAMS | DUAL CONDITIONING TANKS | REVERSE DROP BRUSH
This pattern may require adjustments if using a lane machine that does not have these features



SCAN QR CODE TO
SHARE AND
DOWNLOAD
THIS PATTERN



KEGEL PATTERN LIBRARY APP



PATTERNLIBRARY.KEGEL.NET