

5-1/2" OD, HWDP, INTEGRAL, STANDARD, 7.000" OD x 4.000" ID, DPM-DS55

## HEAVY WEIGHT DRILL PIPE BODY

Nominal OD (in)	5-1/2
Nominal ID (in)	4.000
Pipe Grade	AISI 4145
Heavy Weight Type	STANDARD
HWConstruction	INTEGRAL
Pipe Wall Thickness (in)	0.750
Cross Sectional Area of Pipe Body (in <sup>2</sup> )	11.192
Cross Sectional Area OD (in <sup>2</sup> )	23.758
Cross Sectional Area ID (in <sup>2</sup> )	12.566
Section Modulus (in <sup>3</sup> )	11.764
Polar Section Modulus (in <sup>3</sup> )	23.529
Torsional Strength (lbs/ft)	135,759
Tensile Strength (lbs)	1,343,031
Burst Pressure (psi)	32,351
Collapse Pressure (psi)	28,264

## HEAVY WEIGHT DRILL PIPE CONNECTION

OD (in)	7.000
ID (in)	4.000
Connection	DPM-DS55
Torsional Strength (lbs/ft)	69,059
Tensile Yield Strength (lbs)	1,197,046
Tool Joint/Drill Pipe Torsional Ratio (New)	0.51

## HEAVY WEIGHT DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.75
Closed End Displacement (gal/ft)	1.40
Fluid Capacity (gal/ft)	0.65
Drift Size (in)	3.813
Adjusted Weight (lbs/ft)	48.97

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PST Energy Ltd. accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.